



Main

Device short name	C
Enclosure type	Dust and damp proof weatherproof enclosure for indoor/outdoor
Product specific application	Condensation pump
Switch application	Standard

Complementary

Electrical connection	Screw clamp terminal
Float movement	4.75...9.25 in
Float position	Left
Material	Stainless steel: float/rod Nitrile (Buna-N): seal ring
Motor power hp	3 Hp at 115 V AC, 3 phases 2 Hp at 115 V AC, 1 phase 3 Hp at 230 V AC, 1 phase 5 Hp at 230 V AC, 3 phases 1 hp at 460/575 V AC, 3 phases
Mounting support	Flange
Number of poles	2
Permissible voltage	575 V AC
Switch function	DPST

Environment

NEMA degree of protection	NEMA 4
---------------------------	--------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	9.525 kg

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither TWSS Holding nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.