



## Main

|                           |                                          |
|---------------------------|------------------------------------------|
| Range of product          | Telemecanique Limit switches XC Standard |
| Series name               | Miniature format                         |
| Product or component type | Wireless limit switch                    |
| Device short name         | XCMW                                     |
| Sensor design             | Miniature                                |
| Body type                 | Fixed                                    |
| Head type                 | Plunger head                             |

## Complementary

|                              |                                                                                      |
|------------------------------|--------------------------------------------------------------------------------------|
| Body material                | Plastic                                                                              |
| Head material                | Metal                                                                                |
| Lever material               | Metal                                                                                |
| Fixing mode                  | By 2 screws                                                                          |
| Type of operator             | Spring return roller plunger metal                                                   |
| Switch actuation             | By 30° cam                                                                           |
| Type of approach             | Lateral approach, 2 directions                                                       |
| Communication network type   | ZigBee green power - 2.4 GHz conforming to IEEE 802.15.4                             |
| Electrical composition code  | PW1                                                                                  |
| Emission power               | 3 mW                                                                                 |
| Response time                | <= 2 ms                                                                              |
| Maximum sensing distance     | 100 M in free field<br>300 M with external antenna<br>25 m in industrial environment |
| Contact operation            | Snap action                                                                          |
| Number of steps              | 1                                                                                    |
| Maximum force for tripping   | 50 N                                                                                 |
| Maximum actuation speed      | 0.1 m/s                                                                              |
| Maximum operating rate       | 60 cyc/mn                                                                            |
| Mechanical durability        | 400000 cycles                                                                        |
| Switching operation per hour | 3600                                                                                 |
| Width                        | 30.0 mm                                                                              |
| Height                       | 84 mm                                                                                |
| Depth                        | 16.0 mm                                                                              |
| Net weight                   | 0.046 kg                                                                             |

## Environment

|                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Electromagnetic compatibility         | Radiated emission<br>Immunity for industrial environments<br>Susceptibility to electromagnetic fields - test level: 3 V/m (80...2700 MHz, distance = 20 m)<br>Susceptibility to electromagnetic fields - test level: 10 V/m (80...2000 MHz)<br>Electrostatic discharge immunity test - test level: 6 kV (on contact (on metal parts))<br>Electrostatic discharge immunity test - test level: 8 kV (in free air (in insulating parts)) |
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                                                                                                                                                                                                                                                                                                                                                                                          |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6<br>+/- 10 mm (f= 2...11 Hz) conforming to IEC 60068-2-6                                                                                                                                                                                                                                                                                                                            |
| IP degree of protection               | IP65 conforming to IEC 60529                                                                                                                                                                                                                                                                                                                                                                                                          |
| IK degree of protection               | IK04 conforming to IEC 62262                                                                                                                                                                                                                                                                                                                                                                                                          |
| Ambient air temperature for operation | -25...55 °C                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Ambient air temperature for storage   | -40...70 °C                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Directives                            | 1999/5/EC - R&TTE directive<br>2004/108/EC - electromagnetic compatibility                                                                                                                                                                                                                                                                                                                                                            |
| Standards                             | IEC 60947-1<br>IEC 60947-5-1                                                                                                                                                                                                                                                                                                                                                                                                          |
| Radio agreement                       | IC conforming to RSS[RETURN]FCC conforming to RCM                                                                                                                                                                                                                                                                                                                                                                                     |


## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 3.300 cm  |
| Package 1 Width              | 5.000 cm  |
| Package 1 Length             | 13.000 cm |
| Package 1 Weight             | 61.000 g  |
| Unit Type of Package 2       | S01       |
| Number of Units in Package 2 | 22        |
| Package 2 Height             | 15 cm     |
| Package 2 Width              | 15 cm     |
| Package 2 Length             | 40 cm     |
| Package 2 Weight             | 1.527 kg  |

## Offer Sustainability


|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Dimensions



(1) : 2 fixing holes  $\varnothing 4.2$  mm ( $\varnothing 0.17$  in.)


### Screw Mounting



$$A = 1 \text{ Nm} \pm 0.1$$


$$A = 8.85 \text{ lb.in.} \pm 0.89$$

### Unobstructed Mounting




(1) : Typical values that may be modified by the application environment.

### Mounting in a Metal Cabinet



### Signal Attenuation According to the Material



(1) : Metal structure

(2) : Wall


(3) : Values for indication purposes only

NOTE: Actual values depend on the thickness and nature of the material.

| Material        | Signal attenuation (%) |
|-----------------|------------------------|
| Glass window    | 10...20% (3)           |
| Plaster wall    | 20...45% (3)           |
| Brick wall      | 60% (3)                |
| Concrete wall   | 70...80% (3)           |
| Metal structure | 50...100% (3)          |



## Mounting Tips for Antenna

### Optimized Installation



(1) : Obstacle


The Relay Antenna is used to Bypass an Obstacle and/or Increase the Range



---

Characteristics of Actuation

---



---

Technical Description

---

Functional Diagram, Travel Distance



(1) : Reset

(2) : Set