

Limit switch, Limit switches XC Standard,  
XCPR, metal end plunger, 2NC, snap, Pg13



## Main

|                               |                                                                         |
|-------------------------------|-------------------------------------------------------------------------|
| Range of product              | Telemecanique Limit switches XC Standard                                |
| Series name                   | Standard format                                                         |
| Product or component type     | Limit switch                                                            |
| Device short name             | XCPR                                                                    |
| Sensor design                 | Compact                                                                 |
| Reset                         | With                                                                    |
| Body type                     | Fixed                                                                   |
| Head type                     | Plunger head                                                            |
| Material                      | Plastic                                                                 |
| Body material                 | Plastic                                                                 |
| Head material                 | Zamak                                                                   |
| Fixing mode                   | By the body                                                             |
| Movement of operating head    | Linear                                                                  |
| Type of operator              | Spring return plunger metal                                             |
| Type of approach              | Vertical approach, 1 direction                                          |
| Cable entry                   | 1 entry tapped for Pg 13.5 cable gland, cable outer diameter: 9...12 mm |
| Number of poles               | 2                                                                       |
| Contacts type and composition | 1 NC + 1 NC                                                             |
| Contact operation             | Snap action                                                             |

## Complementary

|                                        |                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Switch actuation                       | On end                                                                                                                                                                                                                                                                                                                                                                 |
| Electrical connection                  | Screw-clamp terminals, clamping capacity: 1 x 0.34...2 x 1.5 mm <sup>2</sup>                                                                                                                                                                                                                                                                                           |
| Contacts insulation form               | Zb                                                                                                                                                                                                                                                                                                                                                                     |
| Positive opening                       | With                                                                                                                                                                                                                                                                                                                                                                   |
| Positive opening minimum force         | 45 N                                                                                                                                                                                                                                                                                                                                                                   |
| Minimum force for tripping             | 15 N                                                                                                                                                                                                                                                                                                                                                                   |
| Maximum actuation speed                | 0.5 m/s                                                                                                                                                                                                                                                                                                                                                                |
| Contact code designation               | A300, AC-15 (U <sub>e</sub> = 240 V), I <sub>e</sub> = 3 A, I <sub>the</sub> = 10 A conforming to EN/IEC 60947-5-1 appendix A<br>Q300, DC-13 (U <sub>e</sub> = 250 V), I <sub>e</sub> = 0.27 A conforming to EN/IEC 60947-5-1 appendix A                                                                                                                               |
| [Ui] rated insulation voltage          | 300 V conforming to UL 508<br>500 V (pollution degree 3) conforming to EN 60947-1<br>300 V conforming to CSA C22.2 No 14                                                                                                                                                                                                                                               |
| Maximum resistance across terminals    | 25 MOhm conforming to IEC 60255-7 category 3                                                                                                                                                                                                                                                                                                                           |
| [Uimp] rated impulse withstand voltage | 6 KV conforming to IEC 60664<br>6 kV conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                         |
| Short-circuit protection               | 10 A cartridge fuse, type gG                                                                                                                                                                                                                                                                                                                                           |
| Electrical durability                  | 5000000 Cycles, DC-13, 120 V, 4 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 Cycles, DC-13, 24 V, 10 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C<br>5000000 cycles, DC-13, 48 V, 7 W, operating rate <60 cyc/mn, load factor: 0.5 conforming to IEC 60947-5-1 appendix C |
| Width                                  | 31 mm                                                                                                                                                                                                                                                                                                                                                                  |
| Height                                 | 65 mm                                                                                                                                                                                                                                                                                                                                                                  |
| Depth                                  | 30 mm                                                                                                                                                                                                                                                                                                                                                                  |

|                               |                        |
|-------------------------------|------------------------|
| Net weight                    | 0.115 kg               |
| Terminals description ISO n°1 | (11-12)NC<br>(21-22)NC |

## Environment

|                                       |                                                                                         |
|---------------------------------------|-----------------------------------------------------------------------------------------|
| Shock resistance                      | 50 gn for 11 ms conforming to IEC 60068-2-27                                            |
| Vibration resistance                  | 25 gn (f= 10...500 Hz) conforming to IEC 60068-2-6                                      |
| IP degree of protection               | IP66 conforming to IEC 60529<br>IP67 conforming to IEC 60529                            |
| IK degree of protection               | IK04 conforming to EN 50102                                                             |
| Overvoltage category                  | Class II conforming to IEC 61140<br>Class II conforming to NF C 20-030                  |
| Ambient air temperature for operation | -25...70 °C                                                                             |
| Ambient air temperature for storage   | -40...70 °C                                                                             |
| Protective treatment                  | TC                                                                                      |
| Product certifications                | CSA[RETURN]UL                                                                           |
| Standards                             | IEC 60204-1<br>EN 60204-1<br>IEC 60947-5-1<br>EN 60947-5-1<br>UL 508<br>CSA C22.2 No 14 |

## Packing Units

|                              |         |
|------------------------------|---------|
| Unit Type of Package 1       | PCE     |
| Number of Units in Package 1 | 1       |
| Package 1 Height             | 19.1 cm |
| Package 1 Width              | 5.2 cm  |
| Package 1 Length             | 58.5 cm |
| Package 1 Weight             | 126.0 g |


## Offer Sustainability

|                                            |                                                                                                                                                                                                                                                                                                                                                                                   |
|--------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status                   | Green Premium product                                                                                                                                                                                                                                                                                                                                                             |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>                                                                                                                                                                                                                                                                                                    |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

## Dimensions




- (1) Tapped entry for Pg 13.5 cable gland
- (2) 2 elongated holes Ø 4.3 x 6.3 mm on 22 mm centres, 2 holes Ø 4.3 on 20 mm centres.
- (3) 2 x Ø 3 holes for support studs, depth 4 mm

---

Mounting with Cable Entry

---

Position of Cable Gland




- (1) Recommended  
(2) To be avoided

---

Wiring Diagrams


---

2-pole NC + NC Snap Action




## Characteristics of Actuation

### Switch Actuation on End



## Functionnal Diagram



- (P) Positive opening point
- (1) NC contact with positive opening operation
- (2) Closed
- (3) Open
- (4) Tripping
- (5) Resetting