



Main

Device short name	XCSA
Enclosure type	Dust and damp proof enclosure for indoor/outdoor Corrosion resistance enclosure for indoor/outdoor

Complementary

[In] rated current	10 A
Actuator	Key
Contact operation	Slow-break, break before make
Contacts type and composition	1 NO/2 NC
Depth	43.94 mm
Enclosure material	metal enclosure
Height	113.54 mm
Locking options description	Without locking of actuator
Number of poles	3
Permissible voltage	300 V AC
Pilot light	LED orange 24/48 V

Environment

Ambient air temperature for operation	-13...158 °F
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.0 cm
Package 1 Width	6.7 cm
Package 1 Length	12.0 cm
Package 1 Weight	635.029 g

Offer Sustainability

Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com