Product data sheet
Characteristics

XCSTE7333
Safety interlock 240 VAC 5 A t XCS



Main

Device short name	XCSTE
Enclosure type	Dust and damp proof enclosure for indoor/outdoor Corrosion resistance enclosure for indoor/outdoor

Complementary

[In] rated current	6 A
[Us] rated supply voltage	120 V
Actuator	Key
Contact operation	Slow-break
Contacts type and composition	2 NC
Depth	33.02 mm
Electromagnet interlocking	Locking on de-energisation and unlocking on energisation of solenoid
Enclosure material	plastic enclosure
Height	93.22 mm
Locking options description	With locking of actuator, unlocking by key operated lock
Number of poles	2
Permissible voltage	300 V AC

Environment

Ambient air temperature for operation	-13…140 °F
IP degree of protection	IP67
NEMA degree of protection	NEMA 4/4X/12

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	3.5 cm
Package 1 Length	9.5 cm
Package 1 Weight	500.0 g

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com