

## Product data sheet

## Characteristics

## XEP3S2W3

Microswitch, Limit switches XC Standard, miniature limit switch, low force cont, flat plunger, 6.35 mm cable clip tags



## Main

|                               |                               |
|-------------------------------|-------------------------------|
| Range of product              | OsiSense XC                   |
| Series name                   | Special format                |
| Product or component type     | Microswitch                   |
| Device short name             | XEP3                          |
| Detector design               | Miniature, DIN 41635 A format |
| Head type                     | Plunger head                  |
| Movement of operating head    | Linear                        |
| Type of operator              | Plunger                       |
| Switch actuation              | On end                        |
| Type of approach              | Vertical approach             |
| Electrical connection         | 6.35 mm cable clip tags       |
| Contacts type and composition | 1 C/O very low force          |
| Contact operation             | Snap action                   |
| Contacts material             | AgNi                          |

## Complementary

|   |  |
|---|--|
| Body material                               | Polyester  |
| Maximum force for tripping                  | 0.25 N lever fixing position in A<br>0.25 N lever fixing position in B<br>0.25 N lever fixing position in C  |
| Minimum release force                       | 0.05 N lever fixing position in A<br>0.05 N lever fixing position in B<br>0.05 N lever fixing position in C  |
| Maximum permissible end of travel force     | 20 N lever fixing position in A<br>20 N lever fixing position in B<br>20 N lever fixing position in C  |
| Tripping point                              | 14.7 Mm lever fixing position in A<br>14.7 Mm lever fixing position in B<br>14.7 mm lever fixing position in C   |
| Maximum differential travel                 | 0.35 Mm lever fixing position in A<br>0.35 Mm lever fixing position in B<br>0.35 mm lever fixing position in C   |
| Minimum over travel                         | 1.1 Mm lever fixing position in A<br>1.1 Mm lever fixing position in B<br>1.1 mm lever fixing position in C  |
| Inter contact distance                      | 0.4 mm   |
| Contact code designation                    | B300, AC-15 (Ue = 240 V, Ie = 1.5 A) conforming to EN/IEC 60947-5-1 appendix A<br>D300, AC-15 (Ue = 240 V, Ie = 0.3 A) conforming to EN/IEC 60947-5-1 appendix A |
| [Ith] conventional free air thermal current | 5 A at 250 V 50/60 Hz  |
| Mechanical durability                       | 50000000 cycles  |
| Width                                       | 10 mm  |
| Height                                      | 16 mm  |
| Depth                                       | 28 mm  |
| Net weight                                  | 5.6 g  |
| Terminals description ISO n°1               | (1-2-4)OC  |

## Environment

|                                       |   |
|---------------------------------------|---|
| IP degree of protection               | IP40  |
| Ambient air temperature for operation | -25...125 °C  |
| Marking                               | CE  |
| Standards                             | IEC 60947-5-1<br>UL 1054<br>CURus<br>EN 60947-5-1<br>EN 61058 |

## Packing Units

|                              |           |
|------------------------------|-----------|
| Unit Type of Package 1       | PCE       |
| Number of Units in Package 1 | 1         |
| Package 1 Height             | 1.000 cm  |
| Package 1 Width              | 2.000 cm  |
| Package 1 Length             | 4.000 cm  |
| Package 1 Weight             | 6.000 g   |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 1.500 cm  |
| Package 2 Width              | 7.000 cm  |
| Package 2 Length             | 13.000 cm |
| Package 2 Weight             | 68.000 g  |
| Unit Type of Package 3       | S01       |
| Number of Units in Package 3 | 100       |
| Package 3 Height             | 15 cm     |
| Package 3 Width              | 15 cm     |
| Package 3 Length             | 40 cm     |
| Package 3 Weight             | 905.000 g |


## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Toxic heavy metal free                     | Yes   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

Dimensions




(1) 13.2 max.

---

[Wiring Diagram](#)

---

Single-pole CO Snap Action



1 : Black


2 : Grey

4 : Blue

---

### Operating Curves

---



(A) Number of cycles  
(B) Current  
1 : Resistive circuit  
2 : Inductive circuit