



Main

Range of product	Telemecanique Photoelectric sensors XU
------------------	--

Series name	Application packaging
-------------	-----------------------

Electronic sensor type	Photo-electric sensor
------------------------	-----------------------

Sensor name	XUM
-------------	-----

Sensor design	Miniature
---------------	-----------

Detection system	Diffuse
------------------	---------

Material	Plastic
----------	---------

Type of output signal	Discrete
-----------------------	----------

Supply circuit type	DC
---------------------	----

Discrete output type	PNP/NPN autodetect IOLINK
----------------------	------------------------------

Discrete output function	1 NO or 1 NC programmable
--------------------------	---------------------------

Electrical connection	Cable
-----------------------	-------

Cable length	2 m
--------------	-----

Product specific application	Diffuse laser Contrast mark reader
------------------------------	---------------------------------------

Emission	Red laser diffuse
----------	-------------------

[Sn] nominal sensing distance	150 mm reflex
-------------------------------	---------------

Complementary

Enclosure material	ABS
Lens material	PMMA
Maximum sensing distance	250 mm diffuse
Output type	Solid state
Output function governance	NO/NC programmable
Add on output	Without, 100 mA
Add on input	Remote teaching
Wire insulation material	PVC
Status LED	1 LED (green) for power ON
[Us] rated supply voltage	12...24 V DC with reverse polarity protection
Supply voltage limits	10...30 V DC
Switching capacity in mA	<= 100 mA (overload and short-circuit protection)
Switching frequency	<= 4000 Hz
Current consumption	<= 30 mA no-load
Maximum delay first up	300 ms
Maximum delay response	125 µs
Maximum delay recovery	300 ms
Setting-up	Sensitivity adjustment with teach mode
Height	34 mm
Length	20 mm
Width	12 mm
Net weight	0.045 kg

Environment

Product certifications	CE
Ambient air temperature for operation	-20...60 °C
Ambient air temperature for storage	-20...80 °C
IP degree of protection	IP67 conforming to IEC 60529

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	7 cm
Package 1 Length	14.2 cm
Package 1 Weight	71 g
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	1.735 kg

Offer Sustainability

For all Reach Rohs enquiries contact us at	sustainability@tesensors.com
--	--

Contractual warranty

Warranty	18 months
----------	-----------