

Photoelectric sensors XUMR, Contrast Mark
reader, White, Sn 12mm, IO-Link, Pigtail M12
15cm



Main

| | |
|-------------------------------|---|
| Range of product | Telemecanique Photoelectric sensors XU |
| Series name | Application packaging |
| Electronic sensor type | Photo-electric sensor |
| Sensor name | XUM |
| Sensor design | Miniature |
| Detection system | Diffuse |
| Material | Plastic |
| Type of output signal | Discrete |
| Supply circuit type | DC |
| Discrete output type | PNP/NPN autodetect IOLINK |
| Discrete output function | 1 NO or 1 NC programmable |
| Electrical connection | 1 pre-cabled male connector M12, 4 pins |
| Cable length | 0.15 m |
| Product specific application | Contrast mark reader |
| Emission | Red, blue and green diffuse |
| [Sn] nominal sensing distance | 12 mm diffuse |

Complementary

| | |
|----------------------------|--|
| Enclosure material | ABS |
| Lens material | PMMA |
| Maximum sensing distance | 15 mm diffuse |
| Output type | Solid state |
| Output function governance | NO/NC programmable |
| Add on output | Without, 100 mA |
| Add on input | Remote teaching |
| Wire insulation material | PVC |
| Status LED | 1 LED (green) for power ON 1 LED (orange) for output state |
| [Us] rated supply voltage | 12...24 V DC with reverse polarity protection |
| Supply voltage limits | 10...30 V DC |
| Switching capacity in mA | <= 100 mA (overload and short-circuit protection) |
| Switching frequency | 10 kHz |
| Current consumption | <= 25 mA no-load |
| Maximum delay first up | 300 ms |
| Maximum delay response | 500 µs |
| Maximum delay recovery | 300 ms |
| Setting-up | Sensitivity adjustment with teach mode Sensitivity by IO-Link |
| Height | 34 mm |
| Length | 20 mm |
| Width | 12 mm |
| Net weight | 0.03 kg |

Environment

| | |
|---------------------------------------|---|
| Product certifications | CE[RETURN]UKCA[RETURN]cULus |
| Ambient air temperature for operation | -20...55 °C |
| Ambient air temperature for storage | -20...80 °C |
| IP degree of protection | IP67 conforming to IEC 60529 IP69K conforming to DIN 40050-9 |

Packing Units

| | |
|------------------------------|---------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 9.1 cm |
| Package 1 Width | 3.1 cm |
| Package 1 Length | 6.1 cm |
| Package 1 Weight | 38 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 30 |
| Package 2 Height | 15 cm |
| Package 2 Width | 15 cm |
| Package 2 Length | 40 cm |
| Package 2 Weight | 1.34 kg |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|