

Photoelectric sensors XU, glass fibre optic for sensor, thru beam, straight, standard, 0.6 m, Sn200mm



#### Main

Range of product	Telemecanique Photoelectric sensors XU
Sensor name	XUY
Sensor design	Fiber design
Sheath type	Standard
[Sn] nominal sensing distance	200 mm XUYAFV
End fitting type	Straight with nickel plated brass, M4 x 0.7

#### Complementary

Electronic sensor type	Photo-electric sensor
Optic fiber material	50 µ glass
Sheath material	PVC + thermo polyolefine
Detection system	Thru beam
Optic fiber length	0.6 m
Minimum bending radius	10 mm
Head mounting	M4 x 0.7
Net weight	0.042 kg

#### Environment

Ambient air temperature for operation	-25...60 °C
---------------------------------------	-------------

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.5 cm
Package 1 Width	13.6 cm
Package 1 Length	13.6 cm
Package 1 Weight	42.9 g
Unit Type of Package 2	S01
Number of Units in Package 2	25
Package 2 Height	15.0 cm
Package 2 Width	15.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.3 kg

#### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisobutyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
For all Reach Rohs enquiries contact us at	<a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>

## Contractual warranty

---

Warranty	18 months
----------	-----------

---