

## XXS30P1AM12

Ultrasonic sensors XX, ultrasonic sensor,  
plastic, cylindrical M30, straight, 1 m, 4...20 mA

## Main

|                               |   |
|-------------------------------|---|
| Range of product              | Telemecanique Ultrasonic sensors XX                                   |
| Sensor type                   | Ultrasonic sensor   |
| Series name                   | General purpose   |
| Sensor name                   | XXS   |
| Sensor design                 | Cylindrical M30   |
| Detection system              | Diffuse   |
| [Sn] nominal sensing distance | 1 M adjustable with remote teach push-button<br>1 m software with kit |
| Material                      | Plastic   |
| Type of output signal         | Analogue  |
| Wiring technique              | 5-wire  |
| Analogue output function      | 4...20 mA   |
| [Us] rated supply voltage     | 12...24 V DC with reverse polarity protection                         |
| Electrical connection         | Male connector M12 5 pins   |
| [Sd] sensing range            | 0.105...1 m   |
| IP degree of protection       | IP65 conforming to IEC 60529<br>IP67                                  |

## Complementary

|   |  |
|---|--|
| Enclosure material                                | PBT  |
| Front material                                    | Epoxy<br>Rubber<br>Resin   |
| Supply voltage limits                             | 10...30 V DC   |
| Function available                                | With synchronisation mode<br>Software configurable                                 |
| [Sa] assured operating distance                   | 0.105...1 m (teach mode)   |
| Blind zone  | 105 mm   |
| Transmission frequency                            | 200 kHz  |
| Repeat accuracy                                   | 0.1 %  |
| Deviation angle from 90° of object to be detected | -10...10 °   |
| Minimum size of detected object                   | Cylinder diameter 1 mm at 600 mm   |
| Status LED  | Output state: 1 LED (yellow)<br>Echo state: 1 LED (green)                          |
| Current consumption                               | 30 mA  |
| Maximum switching capacity                        | 250 Ohm with 12 V DC overload and short-circuit protection<br>850 Ohm with 24 V DC |
| Setting-up  | Teach mode<br>Configurator software  |
| Maximum delay first up                            | 180 ms   |
| Maximum delay recovery                            | 100 ms   |
| Marking   | CE   |
| Threaded length                                   | 39.95 mm   |
| Height  | 30 mm  |
| Width   | 30 mm  |
| Depth   | 64.35 mm   |
| Net weight  | 0.05 kg  |

## Environment

|                                       |  |
|---------------------------------------|--|
| Standards                             | IEC 60947-5-2<br>CSA C22.2 No 14<br>UL 508                 |
| Product certifications                | cULus[RETURN]E2[RETURN]RCM[RETURN]Ecolab                   |
| Ambient air temperature for operation | -25...70 °C  |
| Ambient air temperature for storage   | -40...80 °C  |
| Vibration resistance                  | +/-1 mm conforming to IEC 60068-2-6 (f = 10...55 Hz)       |
| Shock resistance                      | 30 gn in all 3 axes for 11 ms conforming to IEC 60068-2-27 |
| Resistance to electrostatic discharge | 8 kV conforming to IEC 61000-4-2                           |
| Resistance to electromagnetic fields  | 10 V/m level 3 conforming to IEC 61000-4-3                 |
| Resistance to fast transients         | 2 kV conforming to IEC 61000-4-4                           |

## Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 8.5 cm |
| Package 1 Width              | 4.0 cm |
| Package 1 Length             | 8.5 cm |
| Package 1 Weight             | 90.0 g |

## Offer Sustainability

|  |   |
|--|---|
| Sustainable offer status                   | Green Premium product   |
| Circularity Profile                        | No need of specific recycling operations  |
| California proposition 65                  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| For all Reach Rohs enquiries contact us at | <a href="mailto:sustainability@tesensors.com">sustainability@tesensors.com</a>  |


## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|

---


Dimensions

---



## Connections


### Connector Wiring



(1) : Synchronization  
(2) : External setting pushbutton or XXZPB100 remote teach pushbutton.

| Pin number | Wire color | Description     |
|------------|------------|-----------------|
| 1          | BN: Brown  | +12...24VDC     |
| 2          | WH: White  | Input teach     |
| 3          | BU: Blue   | 0 VDC           |
| 4          | BK: Black  | Output          |
| 5          | GY: Grey   | Synchronization |


### Wiring Scheme. Analog Output



(1) : Synchronization

4-20 mA: For 12 VDC, load  $\leq 250 \Omega$   
mA: For 24 VDC, load  $\leq 850 \Omega$

### Wiring for the Synchronization Function (Side by Side Application)



(1) : Synchronization

D1 : 1/8 Sn

BN : Brown

WH : White

BU : Blue

BK : Black


GY : Grey

NOTE: Up to 8 sensors can be synchronized to operate side by side by electrically connecting all pin no.5 (grey) wires together.

To synchronize more than 8 sensors, a PLC output can be used (the pins no.5 must be simultaneously driven by the rising edge of a pulse).


## Performance Curves

### Detection Curve with 100 x 100 mm / 3.94 x 3.94 inches Square Target



(X) : Target distance  
(Y) : Detection limit  
(1) : Blind zone: 105 mm / 4.13 inches  
(2) : Sn max.  
(3) : 100 x 100 mm / 3.94 x 3.94 inches stainless steel plate

### Detection Curve with Round Bar



(X) : Target distance  
(Y) : Detection limit  
(1) : Blind zone: 105 mm / 4.13 inches  
(2) : Sn max.  
(3) : Ø 10 mm / 0.394 inches stainless steel cylinder  
(4) : Ø 25 mm / 0.984 inches stainless steel cylinder