



Main

| | |
|----------------------------|---|
| Range of product | OsiSense XC |
| Series name | Special format |
| Product or component type | Limit switch lever |
| Device short name | ZC2J |
| Product compatibility | XC2J |
| Associated head | ZC2JE04 ZC2JE03 ZC2JE07 ZC2JE02 ZC2JE05 ZC2JE01 ZC2JE06 |
| Movement of operating head | Rotary |
| Type of operator | Rod lever spring return metal (square rod 3 mm, L = 125 mm) |
| Type of approach | Lateral approach |

Complementary

| | |
|------------------|--------------------|
| Switch actuation | By any moving part |
| Positive opening | Without |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | -25...70 °C for standard environment -40...70 °C for low temperature 10...120 °C for high temperature |
| Ambient air temperature for storage | -40...70 °C standard environment -40...70 °C low temperature 10...120 °C high temperature |
| Environmental characteristic | High temperature Low temperature Standard environment |

Packing Units

| | |
|------------------------------|-----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 2.000 cm |
| Package 1 Width | 8.000 cm |
| Package 1 Length | 13.000 cm |
| Package 1 Weight | 38.000 g |
| Unit Type of Package 2 | S01 |
| Number of Units in Package 2 | 100 |
| Package 2 Height | 15.000 cm |
| Package 2 Width | 15.000 cm |
| Package 2 Length | 40.000 cm |
| Package 2 Weight | 3.979 kg |

Offer Sustainability

| | |
|--|---|
| Sustainable offer status | Green Premium product |
| Circularity Profile | No need of specific recycling operations |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| For all Reach Rohs enquiries contact us at | sustainability@tesensors.com |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|