ZCKE619

Limit switch head, Limit switches XC Standard, ZCKE, metal end plunger with protective boot

Main

Range of product	Telemecanique Limit switches XC Standard
Series name	Standard format
Product or component type	Limit switch head
Device short name	ZCKE
Head type	Plunger head
Product compatibility	XCKJ
Associated body	ZCKJ5
	ZCKJD37H7
	ZCKJD35
	ZCKJ4H29
	ZCKJ41H29
	ZCKJ21
	ZCKJ1
	ZCKJD39H29
	ZCKJ4
	ZCKJ6
	ZCKJ11H29
	ZCKJ1H29
	ZCKJ9
	ZCKJ11
	ZCKJ7H29
	ZCKJ5H29
	ZCKJ2H7
	ZCKJD39H7
	ZCKJ8H29
	ZCKJ9H29
	ZCKJ1H7
	ZCKJD31H29
	ZCKJD35H7
	ZCKJ41
	ZCKJD31
	ZCKJD35H29
	ZCKJ9H7
	ZCKJD39
	ZCKJ21H29
	ZCKJ11H7
	ZCKJ21H7
	ZCKJ2H29
	ZCKJ6H29
	ZCKJ4H7
	ZCKJ7H7
	ZCKJ5H7
	ZCKJ7
	ZCKJ8
	ZCKJD37
	ZCKJ2
	ZCKJD31H7
	ZCKJ6H7
	ZCKJ41H7
	ZCKJD37H29
	ZCKJ8H7
Movement of operating head	Linear
Type of operator	End plunger spring return metal (with protective boot)
Type of approach	Vertical approach, 1 direction

Complementary

Switch actuation	On end
Positive opening	With
Head material	Metal

Environment

Ambient air temperature for operation	-25…70 °C
Ambient air temperature for storage	-40…70 °C
Environmental characteristic	Standard environment

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.400 cm
Package 1 Width	4.800 cm
Package 1 Length	9.000 cm
Package 1 Weight	155.000 g
Unit Type of Package 2	S01
Number of Units in Package 2	14
Package 2 Height	15 cm
Package 2 Width	15 cm
Package 2 Length	40 cm
Package 2 Weight	2.346 kg

Offer Sustainability

Sustainable offer status	Green Premium product
Circularity Profile	No need of specific recycling operations
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
For all Reach Rohs enquiries contact us at	sustainability@tesensors.com

Contractual warranty

Warranty	18 months

Telemecanique
Sensors