

0015703

DATA SHEETvalid from:
18.11.2025**ÖLFLEX® 150 CY****LAPP****Application**

ÖLFLEX® 150 CY cables are oil resistant power and control cables designed for the European, North American and Canadian market, for occasional flexible use and fixed installation subject to normal mechanical load conditions. They are also suitable for use in dry, damp or wet areas. If using outdoors, observe the indicated temperature range and use with UV protection.

ÖLFLEX® 150 CY cables are increased resistant to oils and at room temperature largely resistant to acids and alkalis. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

Application range: Plant engineering, industrial machinery, heating and air-conditioning systems

HAR: EN 50565-1 and EN 50565-2

acc. to UL:PVC-sheathed cables for external interconnection or internal wiring of electric and electronic equipment,

Use when getting in contact with oil not above +80 °C (80 °C oil rating)

acc. CSA: CSA AWM I A/B II A/B, cables for internal or external interconnection with or without mechanical load

Design

Design	≤ 60 cores: acc. to EN 50525-2-51 ≥ 61 cores: based on EN 50525-2-51 UL AWM Style 21098, UL 758, CSA C22.2 No. 210-15
Certification	UL AWM Style 21098 (File No. E63634), UL 758 CSA AWM I A/B II A/B (File No. LL53776) ≤ 60 cores: acc. to H05VVC4V5-K acc. to EN 50525-2-51 ≥ 61 cores: based on EN 50525-2-51
	Classification of fire behaviour according to EN 13501-6 and EN 50575 (article/dimension range see www.lappkabel.com/cpr)
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. EN IEC 60228, class 5
Insulation	PVC compound TI2 acc. to EN 50363-3 (UL/CSA 90°C rating)
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to EN 50334
Inner sheath	PVC compound TM 2 acc. to EN 50363-4-1 (UL/CSA 90°C rating)
Screen	braid of tinned copper, coverage = 85% (nominal value)
Outer sheath	PVC compound TM5 acc. to EN 50363-4-1 (UL/CSA 90°C rating) colour: silver grey, similar RAL 7001

Electrical properties at 20 °C

Nominal voltage	EN U ₀ /U: 300/500 V
Rated voltage	UL/CSA: 600 V
Test voltage	core / core: 3000 V AC core / screen: 3000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x outer diameter fixed installation: 6 x outer diameter
Temperature range	occasional flexing: acc. to HAR -5 °C up to +70 °C max. conductor temperature acc. to UL / CSA up to +90 °C max. conductor temperature
	fixed installation: acc. to HAR -40 °C up to +70 °C max. conductor temperature acc. to UL / CSA up to +90 °C max. conductor temperature
Flammability	HAR: acc. to IEC 60332-1-2 resp. EN 60332-1-2 UL: vertical flame test VW-1 CSA: FT1
Oil resistance	TM 5 acc. to EN 50363-4-1 UL: 80 °C rating acc. to UL 758 CSA: CSA 22.2 No. 210-15

AbN
automation

0015703	DATA SHEET	 LAPP
valid from: 18.11.2025	ÖLFLEX® 150 CY	

Tests

acc. to IEC 60811, EN 50395, EN 50396, UL 1581 and CSA 22.2

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see www.lappkabel.com/cpr) are classified acc. to the EU-Regulation no. 305/2011 (CPR).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: LABU / PDC	Document: DB0015703EN	Page 2 of 2
Released: ALTE / PDC	Version: 08	