

0019700	<b>DATA SHEET</b>	 <b>LAPP</b>
valid from: 12.01.2026	<b>ÖLFLEX® CLASSIC 110 ORANGE</b>	

## Application

ÖLFLEX® CLASSIC 110 ORANGE cables are PVC-insulated power and control cables for flexible use and fixed installation for normal mechanical stresses. They are suitable for use in dry, damp and wet areas. If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature.

ÖLFLEX® CLASSIC 110 ORANGE cables are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm<sup>2</sup> of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

### Application range:

Interlocking control circuits acc. to EN 60204-1, electrical lighting and socket circuits for maintenance or repair purposes.

This cable is suitable for torsion application in wind turbines (WTG). The torsional load is limited to applications, as they typically occur in the loop of a wind turbine.

## Design

Design	based on EN 50525-2-51
Certification	EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see <a href="http://www.lappkabel.com/cpr">www.lappkabel.com/cpr</a> )
Conductor	fine wire strands of bare copper acc. to IEC 60228 resp. EN IEC 60228, class 5
Insulation	PVC compound TI2 acc. to EN 50363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor orange cores with black numbers acc. to EN 50334
Cable assembly	cores are stranded in layers
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 with increased requirements acc. to LAPP specification colour: orange, similar RAL 2003

## Electrical properties at 20 °C

Specific volume resistivity	> 20 G Ω x cm
Nominal voltage	U <sub>0</sub> / U: 300 / 500 V
Test voltage	core / core: 4000 V

## Mechanical and thermal properties

Minimum bending radius	occasional flexing: 15 x outer diameter fixed installation: 4 x outer diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temperature fixed installation: - 40 °C up to +80 °C max. conductor temperature
Torsional stress	Torsion movement in wind turbine generators TW-0 (5000 cycles at ≥ +5 °C) TW-1 (2000 cycles at ≥ -20 °C) ±150 °/m at 1 revolution per minute
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2

**Tests** acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396

**General requirements** These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see [www.lappkabel.com/cpr](http://www.lappkabel.com/cpr)) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

**Environmental information** These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

AbN  
automation

Creator: LABU / PDC	Document: DB0019700EN	Page 1 of 1
Released: ALTE / PDC	Version: 08	