

0152005	<b>DATA SHEET</b>	 <b>LAPP</b>
Valid from: 03.01.2019	<b>DIN compensating cable KN 3 L 2x1,5 oval</b>	

## Application

The compensating cable KN 3 L 2 x 1,5 mm<sup>2</sup> is a glass fibre insulated cable which transmits the thermoelectric voltage of NiCr/Ni thermocouples. It is for fixed installation in dry rooms and may only be installed outdoors with UV- and humidity protection and in observation of the max. permitted temperature range.

## Design

Conductor	1.5 mm <sup>2</sup> (48 x 0.20 mm)	
Conductor material	KCA alloying, accuracy class 2 according DIN 43722	
Positive conductor:	Fe (iron)	
Negative conductor:	CuNi (cupronickel)	
Core insulation	Glass fibre covering	
Core identification	Positive conductor:	red marked
	Negative conductor:	green marked
Core layering	Cores parallel next to each other	
Outer sheath	Glass fibre braiding with interwoven green identification thread	

## Electrical properties

Limiting deviation class 2	±100 µV (±2.5 °C) / measuring point temperature +900 °C
----------------------------	---

## Mechanical and thermal properties

Temperature range	occasional flexing:	-25 °C up to +200 °C
Minimum bending radius	occasional flexing:	12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	

AbN  
automation

Creator: TOME/PCM	Document: DB0152005EN	Page 1 of 1
Released: ALTE/PDC	Version: 04	