

0153010	DATA SHEET	 LAPP
Valid from: 01.04.2019	DIN compensating cable KP 9 L 2x1,5 round	

Application

The compensating cable KP 9 L 2 x 1,5 mm² is a PVC insulated cable which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for flexible use and fixed installation in dry and damp rooms. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range.

Design

Conductor	1.5 mm ² (48 x 0.20 mm)	
Conductor material	RCB/SCB alloying, accuracy class 2 according DIN 43722	
	Positive conductor:	Cu (copper)
	Negative conductor:	CuNi (cupronickel)
Core insulation	PVC compound	
Core identification	Positive conductor:	red
	Negative conductor:	white
Core layering	Cores twisted together	
Outer sheath	PVC compound, colour: white	

Electrical properties

Limiting deviation class 2	±60 µV (±5.0 °C) / measuring point temperature +1000 °C
----------------------------	---

Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	

AbN
automation

Creator: TOME/PCM	Document: DB0153010EN	Page 1 of 1
Released: ALTE/PDC	Version: 02	