

0154011	<b>DATA SHEET</b>	 <b>LAPP</b>
Valid from: 09.04.2025	<b>DIN extension cable KE 20 L 2x1,5</b>	

## Application

The extension cable KE 20 L 2 x 1,5 mm<sup>2</sup> is a PVC insulated cable with aluminium foil screen which transmits the thermoelectric voltage of Fe/CuNi thermocouples. It is for flexible use and fixed installation in dry and damp rooms with medium mechanical load. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range. The overlapping foil wrapping screens the cores against electromagnetical interference.

## Design

Conductor	1.5 mm <sup>2</sup> (48 x 0.20 mm)	
Conductor material	LX alloying, accuracy class 2 acc. to DIN 43722	
	Positive conductor:	Fe (iron)
	Negative conductor:	CuNi (cupronickel)
Core insulation	PVC compound	
Core identification	Positive conductor:	red
	Negative conductor:	blue
Cable assembly	Cores twisted together	
Screening	aluminium cladded plastic foil with tinned copper drain wire	
Outer sheath	PVC compound, colour:	blue

## Electrical properties

Limiting deviation class 2	±140 µV (±2.5 °C) / measuring point temperature +500 °C
----------------------------	---

## Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	15 x outer diameter
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2	

AbN  
automation

Creator: LUJU/PCS	Document: DB0154011EN	Page 1 of 1
Released: ALTE/PDC	Version: 03	