



DATA SHEET	0161019
IEC extension cable KE 13 L-SIL 2x1,5 oval	valid from : 01.12.2008

Application

The extension cable KE 13 L-SIL 2 x 1,5 mm² is a silicone and glass fibre insulated cable which transmits the thermoelectric voltage of Fe/CuNi thermocouples. It is for fixed installation in dry rooms. It may only be installed outdoors with UV- and humidity protection and in observation of the max. permitted temperature range.

Design

Conductor	1,5 mm ² (48 x 0,20 mm)
Conductor material	JX alloying, accuracy class 2 according IEC 60584 Positive conductor: Fe (iron) Negative conductor: CuNi (cupronickel)
Core insulation	Silicone compound
Core identification	Positive conductor: black Negative conductor: white
Core layering	Cores parallel next to each other
Outer sheath	Glass fibre braiding with interweaved black identification thread

Electrical properties

Limiting deviation class 2	± 140 µV (± 2,5 °C) / m easuring point temperature +500 °C
----------------------------	--

Mechanical and thermal properties

Temperature range	occasional flexing: -25 °C up to +180 °C
Minimum bending radius	occasional flexing: 12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2

AbN
automation