

0163010	<b>DATA SHEET</b>	 <b>LAPP</b>
Valid from: 01.04.2019	<b>IEC compensating cable KP 9 L 2x1,5 round</b>	

## Application

The compensating cable KP 9 L 2 x 1,5 mm<sup>2</sup> is a PVC insulated cable which transmits the thermoelectric voltage of PtRh/Pt thermocouples. It is for flexible use and fixed installation in dry and damp rooms. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range.

## Design

Conductor	1.5 mm <sup>2</sup> (48 x 0.20 mm)	
Conductor material	RCB/SCB alloying, accuracy class 2 according IEC 60584	
Positive conductor:	Cu (copper)	
Negative conductor:	CuNi (cupronickel)	
Core insulation	PVC compound	
Core identification	Positive conductor:	orange
	Negative conductor:	white
Core layering	Cores twisted together	
Outer sheath	PVC compound, colour:	orange

## Electrical properties

Limiting deviation class 2	±60 µV (±5.0 °C) / measuring point temperature +1000 °C
----------------------------	---

## Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	12 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	

AbN  
automation

Creator: TOME/PCM	Document: DB0163010EN	Page 1 of 1
Released: ALTE/PDC	Version: 02	