

0167514	DATA SHEET	 LAPP
Valid from: 01.04.2019	IEC extension cable KE 9 L-SY 2x1,5	

Application

The extension cable KE 9 L-SY 2 x 1,5 mm² is a PVC insulated cable with steel wire armouring which transmits the thermoelectric voltage of Fe/CuNi thermocouples. It is for flexible use and fixed installation in dry and damp rooms with medium mechanical load. They may only be installed outdoors with UV protection and in observation of the max. permitted temperature range. The steel wire armouring serves as mechanical protection.

Design

Conductor	1.5 mm ² (48 x 0.20 mm)	
Conductor material	JX alloying, accuracy class 2 according IEC 60584	
	Positive conductor:	Fe (iron)
	Negative conductor:	CuNi (cupronickel)
Core insulation	PVC compound	
Core identification	Positive conductor: Negative conductor:	black white
Core layering	Cores twisted together	
Inner sheath	PVC compound, colour:	black
Armouring	Galvanized steel wire braiding	
Outer sheath	PVC compound, colour:	black

Electrical properties

Limiting deviation class 2	±140 µV (±2.5 °C) / measuring point temperature +500 °C
----------------------------	---

Mechanical and thermal properties

Temperature range	occasional flexing:	-5 °C up to +70 °C
Minimum bending radius	occasional flexing:	15 x cable diameter
Flammability	flame retardant in acc. to IEC 60332-1-2 resp. VDE 0482-332-1-2	

AbN
automation

Creator: TOME/PCM Released: ALTE/PDC	Document: DB0167514EN Version: 02	Page 1 of 1
---	--------------------------------------	-------------