

11101500

**DATA SHEET**valid from:  
28.01.2022**ÖLFLEX® DC GRID 100****LAPP****Application**

ÖLFLEX® DC GRID 100 are cables with an insulation and outer sheathing of PVC. They are used for fixed installation in dry or damp areas as well as outdoors, underground and under water.

Application range: connection cable for electrical systems which are operated with direct voltage.

**Design**

Design	based on VDE 0276-603 and IEC TS 61200-1021
Conductor	bare copper, fine wire strand acc. to IEC 60228 resp. EN 60228, class 5, circular
Insulation	PVC compound DI4 acc. to VDE 0276-603
Core identification code	coloured cores, 3 cores: red; white; GNYE 4 cores: red; white; blue; GN/YE
Outer sheath	PVC compound DMV5 acc. to VDE 0276-603 colour: black, similar RAL 9005

**Electrical properties at 20 °C**

Specific volume resistivity	> 20 G Ω x cm
Nominal voltage	conductor – earth: 750 V DC conductor – conductor: 1500 V DC
Operating voltage	conductor – earth: max. 900 V DC conductor – conductor: max. 1800 V DC
Test voltage	core/core: 4000 V AC

**Mechanical and thermal properties**

Minimum bending radius	fixed installation: 12 x outer diameter
Temperature range	fixed installation: -40 °C up to +70 °C max. conductor temp.
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2
UV resistance	acc. to EN 50618 acc. to EN 50620 acc. To EN ISO 4892-2, method A (change of colour allowed)
Ozone resistance	acc. to EN 50396, method B

**Tests**

acc. to EN 60811 resp. IEC 60811, VDE 0472, EN 50395 and EN 50396

**General requirements**

These cables are conform to the EU-Directive 2014/35/EU  
(Low Voltage Directive).

**Environmental information**

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

AbN  
automation

Creator: LABU / PDC	Document: DB11101500EN	Page 1 of 1
Released: ALTE / PDC	Version: 01	