

1125752

DATA SHEETvalid from:
20.11.2024**ÖLFLEX® CLASSIC 110 SY****LAPP****Application**

ÖLFLEX® CLASSIC 110 SY cables are VDE approved power and control cables for occasional flexible use and fixed installation for medium mechanical load conditions. They are also suitable for use in dry, damp or wet areas. Outdoor use: If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature. They are suitable for occasional, non-automated movements. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

The steel wire braid is used for the mechanical protection of the cable.

Application range:

As power and connecting cable in plant engineering and construction, industrial machinery and in heating and air-conditioning systems as well as in areas with high mechanical stress.

Design

Design	based on EN 50525-2-51
Certification	▫ VDE-REG 7030 ▫ limited to following dimension range: 0.5 mm ² - 2.5 mm ² 2 - 65 cores 4 mm ² - 16 mm ² 2 - 7 cores 25 mm ² - 120 mm ² 2 - 5 cores EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see www.lappkabel.com/cpr)
Conductor	fine wire strands of bare copper, acc. to IEC 60228 resp. EN IEC 60228, class 5
Insulation	PVC compound TI2 acc. to EN 50363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to DIN EN 50334
Cable assembly	cores are stranded in layers
Inner sheath	PVC compound TM2 acc. to EN 50363-4-1 colour: silver grey, similar RAL 7001
Braid	Galvanized steel-wires, coverage = 70 % (nominal value)
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 colour: transparent

Electrical properties at 20 °C

Nominal voltage	U ₀ / U: 300/500V
Test voltage	core / core: 4000 V AC core / screen: 4000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x outer diameter fixed installation: 6 x outer diameter
Temperature range	occasional flexing: - 5 °C up to +70 °C max. conductor temp. fixed installation: - 40 °C up to +80 °C max. conductor temp.
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2

Tests acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396

General requirements These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see www.lappkabel.com/cpr) are classified
in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

AbN
automation

Creator: MAIH / PDC	Document: DB1125752EN	Page 1 of 2
Released: ALTE / PDC	Version: 08	

1125752	DATA SHEET	 LAPP
valid from: 20.11.2024	ÖLFLEX® CLASSIC 110 SY	

