

1136752

DATA SHEETvalid from:
21.05.2024**ÖLFLEX® CLASSIC 115 CY****LAPP****Application**

ÖLFLEX® CLASSIC 115 CY cables are control cables for occasional flexible use and fixed installation under medium mechanical load conditions. They are also suitable for use in dry, damp or wet areas. If using outdoors, observe the indicated temperature range and use with UV protection. They are largely resistant to acids, alkalis and certain oils at room temperature.

ÖLFLEX® CLASSIC 115 CY cables are suitable for occasional, non-automated movements. They meet the requirements for slow rotational movements, such as in the loop of a wind turbine. The maximum tensile load is 15 N/mm² of conductor cross-section during installation and operation. Compulsory guidance is not permitted.

The screening braid protects against interference from electrical fields.

Application range:

Control units for machine tools, conveyor systems, measurement and control technology, office machines and systems for data processing. This cable is suitable for torsion application in wind turbines (WTG). The torsional load is limited to applications, as they typically occur in the loop of a wind turbine.

Design

Design	based on EN 50525-2-51
Certification	EN 13501-6 and EN 50575 Classification of fire behaviour (article/dimension range see www.lappkabel.com/cpr)
Conductor	fine wire strands of bare copper acc. to IEC 60228 resp. EN 60228, class 5
Insulation	PVC compound TI2 acc. to EN 50363-3 with increased requirements acc. to Lapp specification
Core identification code	acc. to VDE 0293-1, with or without GN/YE ground conductor black cores with white numbers acc. to EN 50334
Stranding	cores are stranded in layers
Wrapping	plastic foil
Screen	braid of tinned copper, coverage = 85 % (nominal value)
Outer sheath	PVC compound TM2 acc. to EN 50363-4-1 with increased requirements acc. to LAPP specification colour: silver grey, similar RAL 7001

Electrical properties at 20 °C

Specific volume resistivity	> 20 G Ω x cm
Transfer impedance	max. 250 mΩ/m (at 30 MHz)
Nominal voltage	U ₀ / U: 300 / 500 V
Test voltage	core / core: 4000 V AC core / screen: 2000 V AC

Mechanical and thermal properties

Minimum bending radius	occasional flexing: 20 x outer diameter fixed installation: 6 x outer diameter
Temperature range	occasional flexing: -5 °C up to +70 °C max. conductor temp. fixed installation: -40 °C up to +80 °C max. conductor temp.
Torsional stress	Torsion movement in wind turbine generators TW-0 (5000 cycles at ≥+5 °C) TW-1 (2000 cycles at ≥-20 °C) ±150 °/m at 1 revolution per minute
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2

Tests**General requirements**

acc. to IEC 60811 resp. EN 60811, EN 50395, EN 50396

These cables are conform to the EU-Directive 2014/35/EU
(Low Voltage Directive).A part of these cables (see www.lappkabel.com/cpr) are classified
in accordance with the EU-Regulation no. 305/2011 (CPR).**Environmental information**

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

AbN
Automation

Creator: ALTE / PDC	Document: DB1136752EN	Page 1 of 1
Released: LABU / PDC	Version: 08	