

1161005

Data sheet

Valid from:
12.02.2025Thermocouple cable K GL-GL-S NiCr/Ni 2x0.22
IEC**LAPP**

Application

The thermocouple cable K GL-GL-S Fe/CuNi 2x0.22 mm² is a E-glass wrapped thermocouple cable type K, which transmits the thermoelectric voltage of NiCr/Ni-thermocouples. It is for flexible use and fixed installation in dry rooms. They may only be installed outdoors with UV-protection and in observation of the maximum permitted temperature range.

Design

Conductor	0,22 mm ² (7 x 0,20 mm)
Conductor material	K alloys, according to IEC 60584-1 Positive conductor: NiCr (Nickel chromium) Negative conductor: Ni (Nickel)
Core insulation	E-glass
Core identification	Positive conductor: green Negative conductor: white
Core layering	Cores twisted together
Outer braid	Braid made of E-glass, with green tracer yarn
Armouring	Protective braid made of galvanized steel wires

Electrical properties

Limiting deviation	±2,5°C (acc. to IEC 60584-1)
Thermocouple tolerances	-40°C up to 1200°C (acc. to IEC 60584-1)
Test voltage	500 V

Mechanical and thermal properties

Minimum bending radius	occasionally flexing: 15 x cable diameter fixed installation: 7,5 x cable diameter
Temperature range	occasionally flexing: -25°C up to +350°C fixed installation: -50°C up to +350°C

AbN
automation