


UNIRAIL S – EN 50264-3-1 600 V – type M – EN 50200

UNIKA (Italy) - EN 50264-3-1 600 V 6 M - EN 50200 PH120 - code



TECHNICAL DATA

Temperature rating up to and including 90°C

Very low temperatures resistance (-40°C)

Resistance to ozone, oils, fuels, acids and alkali

Bending radius: refer to EN 50343 table 16

Range of approval:

According to table 1 (cross-section 1 ÷ 400 mm²) of EN 50264-3-1 for cables rated 600V (see IMQ test certificate) with fire resisting time not below 120 min

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB801	1	2,4 ÷ 2,8	17
RB802	1,5	2,8 ÷ 3,3	23
RB803	2,5	3,2 ÷ 3,8	33
RB804	4	3,8 ÷ 4,4	47
RB805	6	4,2 ÷ 5,0	67
RB806	10	5,1 ÷ 5,9	106
RB807	16	6,1 ÷ 7,2	158
RB808	25	7,8 ÷ 9,1	248
RB809	35	9,0 ÷ 10,6	331
RB810	50	10,6 ÷ 12,4	474
RB811	70	12,5 ÷ 14,6	655
RB812	95	13,9 ÷ 16,3	871
RB813	120	15,7 ÷ 18,4	1095
RB814	150	17,6 ÷ 20,6	1363
RB815	185	19,6 ÷ 22,9	1699
RB816	240	22,2 ÷ 26,0	2197
RB817	300	24,6 ÷ 28,8	2689
RB818	400	28,1 ÷ 32,9	3800

Out of the scope of the Standard.

Item n°	Cross-section [mm ²]	Diameter [mm]	Cable mass [kg/km]
RB819	0,50	2,2	10
RB820	0,75	2,4	13

CONSTRUCTION

Type: single core cable unsheathed, fire resistant

Conductor: tinned copper conductor according to class 5 EN 60228

Tape: mica tape

Insulation: crosslinked compound, type EI109 according to Standard EN 50264-1, colour red if not otherwise stated

Marking: UNIKA (Italy) – EN 50264-3-1 600V *cross-section* M – EN 50200 PH120 - *traceability code*

Fire safety: Cables are classified in compliance to the highest requirements established by **hazard level HL3** into Standard EN 45545-2 for indoor cables (EL1A) and outdoor cables (EL1B)

Add the following letter after the item number for colours different from red
G: yellow/green
Y: grey
B: blue
W: brown
H: white
K: black

AbN
automation

The characteristics of the products described in the data sheet, do not constitute any contractual binding. UNIKA spa reserves the right to change the specifications without any notice. Partial or total reproduction of this document is forbidden.