

1600000

DATA SHEETvalid from:
2022-08-26**NYM****LAPP****Application**

NYM are single or multicore PVC sheathed cables intended for fixed installation over, on, in and under the plastering in dry, damp and wet locations as well as in masonry and concrete, except direct embedding in vibrated or compressed concrete. They are suitable for outdoor use if protected against direct sunlight.

Design

Design	acc. to DIN VDE 0250-204 (VDE 0250-204)
Certification	The cable is marked with the <VDE>-sign or VDE-identification thread. Classification of fire behaviour according to EN 13501-6 and EN 50575 (article/dimension range see www.lappkabel.com/cpr)
Conductor	up to 10 mm ² : single-wire copper conductor acc. to IEC 60228 resp. EN 60228, Class 1 from 16 mm ² : multi-wire copper conductor acc. to IEC 60228 resp. EN 60228, Class 2
Insulation	PVC compound type TI1 acc. DIN VDE 0281-1 (VDE 0281-1)
Core identification code	up to 5 cores: colour-coded acc. VDE 0293-308 (VDE 0293-308) with resp. without GN-YE protective conductor from 6 cores: black cores with white numbers acc. EN 50334 (VDE 0293-334) Coating: filling compound over the core assembly
Outer sheath	PVC compound type TM1 acc. DIN VDE 0281-1 (VDE 0281-1) colour: grey

Electrical properties at 20 °C

Nominal voltage	U ₀ /U: 300/500 V
Test voltage	2000 V AC

Mechanical and thermal properties

Minimum bending radius	4 x outer diameter
Temperature range	during installation: +5 °C to +60 °C fixed installation: -40 °C to +70 °C at conductor: max. +70 °C
Flammability	flame retardant acc. to EN 60332-1-2 resp. IEC 60332-1-2

General requirements

These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive)
These cables (see www.lappkabel.com/cpr) are classified
in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Note

Trade product, no Lapp product

AbN
automation

Creator: PESA / PDC	Document: DB1600000EN	Page 1 of 1
Released: ALTE / PDC	Version: 06	