

1600804	DATA SHEET	 LAPP
valid from: 2024-08-26	H07ZZ-F (X07ZZ-F)	

Application

H07ZZ-F (X07ZZ-F) are halogen-free, heat-resistant flexible cables for heavy stress and especially for applications where low smoke density and low emission of corrosive gases are required at in case of fire. Suitable for connection with equipment and machine tools, where cables for heavy mechanical stress are required. In dry, damp or wet rooms. Also for installation e.g. on plaster in temporary buildings and residential barracks.

Design

Design	acc. to EN 50525-3-21
Certification	The cable is characterized with the <HAR> HAR-sign or HAR-identification thread.
Conductor	Classification of fire behaviour according to EN 13501-6 and EN 50575 (article/dimension range see www.lappkabel.com/cpr)
Insulation	fine-wire copper conductor acc. to IEC 60228 resp. EN 60228, class 5
Core identification code	halogen-free rubber compound EI8 acc. to EN 50363-5 up to 5 cores: colour-coded acc. to VDE 0293-308 with or without GN-YE ground conductor starting at 6 cores: black cores with white numbers with GN-YE ground conductor acc. to EN 50334
Outer sheath	for cable up to 50 mm ² : single-layered: EM 8 acc. to EN 50363-6 for cable starting at 70 mm ² : double-layered: inner layer EM 8 or EM 10 acc. to EN 50363-6 outer sheath: EM 8 acc. to EN 50363-6

Electrical properties at 20 °C

Nominal voltage	U ₀ /U: 450/750 V
Test voltage	A/A: 2500 V AC

Mechanical and thermal properties

Minimum bending radius	4 to 8 x outer diameter acc. to DIN EN 50565-1
Temperature range	occasional flexing: -5 °C to +90 °C max. conductor temperature fixed installation: -40 °C to +90 °C max. conductor temperature
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 no flame propagation acc. to IEC 60332-3-24 resp. EN 60332-3-24
Halogen free	acc. to EN 50525-1 Appendix B and C
Corrosivity of gases	acc. to IEC 60754-2 resp. EN 60754-2
Smoke density	acc. to IEC 61034-2 resp. EN 61034-2
Ozone resistance	acc. to EN 50363-6, EN 60811-403 method A, EN 50396 8.1.3 method B
Oil resistance	acc. to EN 50363-6, test method acc. to EN 60811-404

Tests

General requirements These cables are conform to the EU-Directive 2014/35/EU (Low Voltage Directive).

A part of these cables (see www.lappkabel.com/cpr) are classified in accordance with the EU-Regulation no. 305/2011 (CPR).

Environmental information These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Note

Trade product, no Lapp product

AbN
automation

Creator: PESA/PDC	Document: DB1600804EN	Page 1 of 1
Released: ALTE/PDC	Version: 09	