


2170371

DATA SHEETvalid from:
25.11.2022**UNITRONIC® BUS ASI LD G YE 2x2,5****LAPP****Application**

Field of Use:	Communication at sensor/actuator level. The yellow cable is used to carry control data and DC power supply on the same wire.
Performance:	The UNITRONIC® BUS ASI LD 2 x 2.5 (Long Distance) allows even modules located further away to be connected. AS-i power supplies can be reduced.
Characteristics:	halogen free, flame retardant, UV resistant, oil resistant and largely resistant to acids, alkalies and certain oils
Applications:	The UNITRONIC® BUS ASI LD 2 x 2.5 is downwards-compatible with version 1.5.

**Design**

Conductor	fine-wire stranded, tinned copper 2.5 mm ²
Insulation	rubber compound core diameter: ca. 2.5 mm
Core identification code	brown, blue
Stranding	2 cores parallel deviation, brown core assembled in line with leading edge
Outer sheath	rubber compound yellow, similar RAL 1012 outline and dimensions acc. to IEC 62026-2

Electrical properties at 20 °C

Loop resistance	max. 16,42 Ω/km
Insulation resistance	min. 1 MΩxkm
Mutual capacitance	max. 80 nF/km (at 167 kHz)
Inductance	0,85 mH/km ± 0,45 mH/km (at 167 kHz)
Characteristic impedance	105 Ω ± 35 Ω (at 167 kHz)
Signal propagation time	≤ 8.3ns/m (at 167 kHz)
Maximum operating voltage	AS-i: 300 V
Nominal voltage	EN/IEC: 32 V DC
Test voltage	core/core: 1500 V

Mechanical and thermal properties

Minimum bending radius	fixed installation: occasional flexing:	3x outer diameter 6x outer diameter
Temperature range	fixed installation: occasional flexing:	-40 °C up to +85 °C -25 °C up to +85 °C
Halogen free	acc. to IEC 60754-1 resp. EN 60754-1	
Weather and UV resistance	acc. to ISO 4892-2, method A	
General requirements	This cable is conform to EU-Directive 2014/35/EU (Low Voltage Directive) and to EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances).	
Environmental information	These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).	

AbN
automation

2170371

DATA SHEET

valid from:
25.11.2022

UNITRONIC® BUS ASI LD G YE 2x2,5



Dimensions

Dimensions acc. to IEC 62026-2

