


2170925	DATA SHEET	
valid from: 26.10.2023	ETHERLINE® T1 FLEX Y 1x2x26/7AWG	

Application

Field of use:	Flexible Industrial Ethernet cable for generic cable system acc. to ISO/IEC 11801 and EN 50173. Suitable for occasional flexing. Meeting the transmission requirements of IEC 61156-12, T1-C (Downwards compatible to T1-A-100).
Performance:	1-pair, overall braid and foil screened symmetrical cable (SF/UTP), having a nominal impedance of 100 Ω, supporting a bandwidth of 100 Mbit/s (e.g. 10BASE T1, 100BASE-T1) over up to 15 m.
Characteristics:	flame retardant
Applications:	10BASE-T1 (IEEE 802.3cg), 100BASE-T1 (IEEE 802.3bw) and other



Design

Certification	E63634 cRUus AWM Style 2095 AWM I A/B 80°C 300V FT2 acc. to UL 758 & CSA 22.2 No. 210
Conductor	stranded bare copper 26/7 AWG (0.14 mm ²)
Insulation	foam-skin polyolefine core diameter: max. 1.09 mm
Core identification code	white/blue
Stranding	two cores stranded to pair (with filling elements)
Taping	plastic tape (optional)
Screen	plastic laminated aluminium foil (overlapping) on top: braid of tinned copper wires (coverage: nom. 85 %)
Outer sheath	PVC (Polyvinylchloride) green, similar to RAL 6018 outer diameter: nom. 4.6 mm (± 0.3 mm)

Electrical properties at 20 °C

Loop resistance	20 °C:	≤ 28 Ω/100 m
Test voltage	core/core:	2000 V
	core/screen:	2000 V
Rated voltage	UL:	300 V acc. to UL 758
Maximum operating voltage	IEC/EN:	125 V (not intended to be used in conjunction with low impedance sources, such as power grids)
Insulation resistance	20 °C:	≥ 5 GΩxkm
Mutual capacitance	1 kHz:	nom. 42 nF/km
Capacitance unbalance	1 kHz:	≤ 1200 pF/km
Transfer impedance	Grade 1b acc. to IEC 61156-12	
	0.1 MHz:	≤ 30 mΩ/m
	1 MHz:	≤ 30 mΩ/m
	10 MHz:	≤ 20 mΩ/m
	20 MHz:	≤ 60 mΩ/m

AbN
automation

Creator: KIOS / PDC	Document: DB2170925EN	Page 1 of 2
Released: ALTE / PDC	Version: 01	

2170925	DATA SHEET	
valid from: 26.10.2023	ETHERLINE® T1 FLEX Y 1x2x26/7AWG	

Coupling attenuation	Type I acc. to IEC 61156-12	
	0.1 MHz:	≥ 110 dB
	1 MHz:	≥ 100 dB
	10 MHz:	≥ 90 dB
	30 MHz:	≥ 85 dB
	100 MHz:	≥ 85 dB
	1000 MHz:	≥ 65 dB
Velocity of propagation	100 MHz:	nom. 0.77 c

Transmission properties at 20°C

The transmission characteristics meet the requirements of IEC 61156-12, T1-C. The table contains informative values at key frequencies. Values in brackets are for further studies (ffs).

Frequency	(max.) Phase delay	(max.) Attenuation	(min.) TCL Level 1	(min.) EL TCTL Level 1	Char. Impedance	(min.) RL
f [MHz]	[ns/ 100 m]	[dB/ 100 m]	[dB]	[dB]	[Ohm]	[dB]
0.1	(648)	(2.0)	(40.0)	(53.0)	—	(10.0)
1	570	3.1	40.0	40.0	—	20.0
2	559	4.1	35.5	34.0	—	21.5
4	552	5.6	31.0	28.0	—	23.0
10	545	8.7	25.0	20.0	—	25.0
20	542	12.3	20.5	14.0	—	25.0
62.5	539	21.9	13.1	6.0	—	21.5
100	538	27.8	10.0	6.0	100 ± 5	20.1
200	537	39.7	7.0	6.0	—	18.0
500	536	64.1	7.0	6.0	—	15.2
600	535	70.7	7.0	6.0	—	14.7

Mechanical and thermal properties

Minimum bending radius	fixed installation:	4× outer diameter
	occasional flexing:	8× outer diameter
Temperature range	fixed installation:	-40 °C up to +80 °C
	occasional flexing:	-20 °C up to +60 °C
	UL:	80 °C acc. to UL 758
Flammability	flame retardant acc. to IEC 60332-1-2 resp. EN 60332-1-2 FT2 horizontal flame test acc. to UL 1581 §1100	

General requirements

These cables are conform to the EU-Directive 2011/65/EU (RoHS, Restriction of the use of certain hazardous substances) and the LV-Directive 2014/35/EU (Low voltage Directive).

Environmental information

These cables meet the substance-specific requirements of the EU Directive 2011/65/EU (RoHS).

Creator: KIOS / PDC	Document: DB2170925EN	Page 2 of 2
Released: ALTE / PDC	Version: 01	