

HITRONIC® POF DUPLEX HEAVY PE-PUR

DB28030002EN
valid from: 23.12.2016

1. Product Description

Cable designation: J-V2Y(ZN)11Y 2P980/1000

2. Application

HITRONIC® POF DUPLEX HEAVY PE-PUR are POF duplex core cables with heavy reinforced PUR outer sheath. They are designed for optical signal transmission in dry rooms under heavy mechanical stress in industrial environments and under increased tensile load. The cables are suitable for direct connector assembly.

3. Cable Design



Fibre type	Polymer optical fibre (POF)		
Cable core	Polymethyl methacrylate cores with fluoropolymer cladding		
Buffer coating	Polyethylene (PE)		
Strain relief	Aramid yarns, longitudinal		
Outer sheath	Polyurethane (PUR), increased sheath wall thickness		
Colours of buffer coating	Black/Orange		
Colour of outer sheath	Orange, similar RAL 2003		

4. Optical and Physical Properties of Fibre

Attenuation coefficient	@ 650 nm	dB/km	≤ 160
	@ 660 nm	dB/km	≤ 230
Bandwidth	@ 650 nm	MHz · 100m	≥ 10
Numerical aperture			0.5 ± 0.05
Core diameter		µm	980 ± 2
Cladding diameter		µm	1000 ± 2

5. Thermal Properties

Operating temperature	-40°C to +70°C
Installation temperature	-10°C to +50°C
Storage temperature	-40°C to +70°C

AbN
automation

Originator: CHIL / PDC approved: HAPF / PDC	Document: DB28030002EN	page 1 of 2
--	------------------------	-------------

HITRONIC® POF DUPLEX HEAVY PE-PUR

DB28030002EN
valid from: 23.12.2016

6. Mechanical Properties

Number of fibres	2	
Fibre diameter	2.2 mm	
Outer diameter	8.0 mm	
Cable weight	57 kg/m	
Min. bending radius	fixed installation	10 x cable ø
Max. tensile strength	long term	130 N
	short term	400 N
Max. crush resistance	long term	200 N/dm
	short term	2000 N/dm

7. Chemical Properties

PE buffer	Non-aging, halogen free, good stability against acids and alkalis
PUR outer sheath	Flame retardant, halogen free

8. Approvals

This cable is conform to the EU-Directive 2011/65/EU:
RoHS (Restriction of the use of hazardous substances)

9. Product Range Overview

Part number	Article designation	No. of Fibres	Outer ø (mm)
28030002	HITRONIC® POF DUPLEX HEAVY PE-PUR	2	8.0