

381166828	<b>DATA SHEET</b>	
Valid from: 31.07.2025	<b>EPIC® H-BE 010 FS</b>	

## Description

- Standard inserts with screw termination
- The EPIC® H-BE series is suitable for applications that require a reliable connection when working with high voltages and currents



Images may vary

## General Characteristics

Series	H-BE 10
Version	Female
Design Size	10B
Number of Contacts	10 + PE
Wire Protection	Yes
Termination Methods	Screw termination: 0.75–2.5 mm <sup>2</sup> /AWG 18-14
Temperature Range	-40°C up to +125°C

## Mechanical Characteristics

Cycle of mechanical operation	≥ 500
Tightening torque contact screw	0.5 Nm
Stripping length	7 mm

## Electrical Characteristics

Rated Voltage, IEC	500 V
Rated Voltage, UL & CSA	600 V
Rated Impulse Voltage	6 kV
Rated Current, IEC	16 A
Rated Current, UL & CSA	16 A
Contact Resistance	≤ 1 mΩ
Pollution degree	3

## Materials and Surfaces

Contacts	Copper alloy, hard-silver plated
Insulating Body	PC
Flammability Class according to UL 94	V-0

AbN  
automation

Creator: TODV1/BU EPIC Released: THBO1/BU EPIC	Document: DB381166828EN Version: 01	Page 1 of 3
---	--	-------------

381166828	<b>DATA SHEET</b>	
Valid from: 31.07.2025	<b>EPIC® H-BE 010 FS</b>	


**Certifications**

UL- Certification, E-File-Number E75770


**Standard**

Safety Standard IEC 61984, IEC 60664-1  
UL 1977  
CSA 22.2 182.3

**Technical Drawings**



	a	b	e	g	c	d	f	m
[mm]	16.5	32.5	64.5	34	16.8	34.8	64.5	34



Pin assignment

381166828	<b>DATA SHEET</b>	
Valid from: 31.07.2025	<b>EPIC® H-BE 010 FS</b>	



Industrial machinery and plant engineering



Robust



Temperature-resistant

**Info**

Multifunctional insert for versatile applications

**Application range**

Mechanical engineering  
Light & sound technology  
Plastics industry

**Remark**

Photographs are not to scale and do not represent detailed images of the respective products.

AbN  
automation

Creator: TODV1/BU EPIC Released: THBO1/BU EPIC	Document: DB381166828EN Version: 01	Page 3 of 3
---	--	-------------