

381166844	DATA SHEET	
Valid from: 17.06.2025	EPIC® H-BS 006 FS	

Description

- Inserts for high currents.
- High rating for currents up to 35 A
- Screw termination up to a conductor cross section of 6 mm²



Images may vary

General Characteristics

Series	H-BS 6
Version	Female
Design Size	16B
Number of Contacts	6 + PE
Wire Protection	No
Termination Methods	Screw termination: 1.5 – 6 mm ² /AWG 16-10
Temperature Range	-40°C up to +125°C

Mechanical Characteristics

Cycle of mechanical operation	≥ 500
-------------------------------	-------

Electrical Characteristics

Rated voltage conductor-earth, IEC	400 V
Rated voltage conductor-conductor; IEC	690 V
Rated voltage, UL/CSA	600 V
Rated Impulse Voltage	6 kV
Rated Current, IEC	35 A
Contact Resistance	≤ 1 mΩ
Pollution degree	3

Materials and Surfaces

Contacts	Copper alloy, hard-silver plated
Insulating Body	PC
Flammability Class according to UL 94	V-0

Standard



Safety Standard	IEC 61984, IEC 60664-1
-----------------	------------------------

AbN
automation

Creator: TODV1/BU EPIC Released: THBO1/BU EPIC	Document: DB381166844EN Version: 00	Page 1 of 3
---	--	-------------

381166844	DATA SHEET	
Valid from: 17.06.2025	EPIC® H-BS 006 FS	

Technical Drawings



Pin assignment

381166844	DATA SHEET	
Valid from: 17.06.2025	EPIC® H-BS 006 FS	



Industrial machinery and plant engineering



Robust



Temperature-resistant

Info

Standard insert for currents up to 35A

Application range

Plant engineering
 Mechanical engineering
 Drive systems

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

AbN
automation

Creator: TODV1/BU EPIC Released: THB01/BU EPIC	Document: DB381166844EN Version: 00	Page 3 of 3
---	--	-------------