

44420120

DATA SHEET

Valid from:
17.09.2018

EPIC® SIGNAL M23 12E/12P D-SUB



LAPP

Description

- Inserts for M23 circular connectors
- Efficient assembling due to the use of D-Sub contacts-on-reel



General characteristics

Series	SIGNAL M23
Version	E-part = rotation to the right (clockwise) / P-part = rotation to the left (anticlockwise)
Number of contacts	12
Termination method	Crimp termination
Termination cross-section	0,08 - 0,56 mm ²
Temperaturbereich	-25 to +125 °C
Contacts included	no

Product variations

Article no.	Version	Suitable contacts	PU
44420120	E-Part	male D-Sub crimp-contacts on reel	5
44420121	E-Part	male D-Sub crimp-contacts on reel	20
44420122	E-Part	female D-Sub crimp-contacts on reel	5
44420123	E-Part	female D-Sub crimp-contacts on reel	20
44420124	P-Part	male D-Sub crimp-contacts on reel	5
44420125	P-Part	male D-Sub crimp-contacts on reel	20
44420126	P-Part	female D-Sub crimp-contacts on reel	5
44420127	P-Part	female D-Sub crimp-contacts on reel	20

Mechanical characteristics

Cycles of mechanical operation	50
--------------------------------	----

Electrical characteristics

Rated voltage, IEC	100 V
Rated impulse voltage	1,5 kV
Rated current	4 A
Contact resistance	< 4 mOhm
Pollution degree	3

Materials and surfaces



Insert	PA
--------	----

Standards

Safety Standard	IEC61984
-----------------	----------

AbN
automation

Technical Drawings



Good chemical resistance



Industrial machinery and plant engineering



Mechanical resistance



Assembly time



Robust



Wind Energy



Variety of approval certifications

44420120	DATA SHEET	 LAPP
Valid from: 17.09.2018	EPIC® SIGNAL M23 12E/12P D-SUB	

DATA SHEET



Info

For D-Sub ribbon contacts

Application range

Plant engineering

Measurement and control technology

Apparatus construction

Remark

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise)

Photographs are not to scale and do not represent detailed images of the respective products.

AbN
automation