

52104200	<b>DATA SHEET</b>	
Valid from: 24.11.2023	<b>SKINDICHT® MA-M/PG</b>	

The SKINDICHT® MA-M/PG is a flange reducer from a metric outer thread to an inner PG thread.




<b>Components</b>	<b>Brass</b>	<b>brass lead-free</b>
Material	brass, nickel-plated	brass lead-free, nickel-plated

**Technical features:**

External thread	M16x1.5 up to M63x1.5 acc.to EN 60423
Internal thread	PG7 up to PG42 acc. to DIN 40430
Temperature range	-60°C up to +200°C

**Norm references:**



External thread M	Internal thread PG	Diameter Ø A mm	Length C mm	Thread Length D mm	Article No. brass	Article No. Brass lead-free
M16x1,5	PG 7	18	7,5	5	52104200	52104200LF
M20x1,5	PG 9	22	9	6	52104210	52104210LF
M25x1,5	PG 11	27	10	7	52104220	52104220LF
M25x1,5	PG 13,5	27	10	7	52104230	52104230LF
M25x1,5	PG 16	27	10	7	52104240	52104240LF
M32x1,5	PG 16	34	11	8	52104250	52104250LF
M32x1,5	PG 21	34	11	8	52104260	52104260LF
M40x1,5	PG 21	43	11,5	8	52104270	52104270LF
M50x1,5	PG 29	53	12,5	9	52104280	52104280LF
M63x1,5	PG 36	66	14	10	52104290	52104290LF
M63x1,5	PG 42	66	14	10	52104300	52104300LF

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.



Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB52104200EN Version: 06	Page 1 of 1
---	---------------------------------------	-------------