


54001610	DATA SHEET	
Valid from: 03.07.2018	SKINDICHT® BL with O-RING	

The SKINDICHT® BL with O-Ring installed, is used wherever already existing housing holes are not yet required or no longer required. The blind plug is equipped with a screwing slit, with makes installation significantly easier.



Dimension table:

Part. Nr.	PG	ØA [mm]	C [mm]	D [mm]	O-Ring
54001610	PG 7	14	8	5	10 x 1,5
54000071	PG 9	17	9	6	13 x 1,5
54000040	PG 11	20	9	6	16 x 1,5
54001630	PG 13,5	22	9,5	6,5	18 x 1,5
54001640	PG 16	24	9,5	6,5	20 x 1,5
54001660	PG 21	30	11	7	26 x 2
54001620	PG 29	39	12	8	34 x 2
54001650	PG 36	50	15	9	44 x 2
54001670	PG 42	57	16	10	50 x 2
54001680	PG 48	64	16	10	55 x 2

Material: nickel plated brass
O-Ring: NBR

Protection class: with O-Ring IP 68

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

ALN
automation

Creator: PDP Released: DAMU1/PDP	Document: DB54001610EN Version: 01	Page 1 of 1
-------------------------------------	---------------------------------------	-------------