

55501981	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LGF-2-M	

SILVYN® LGF-2-M is a two part conduit gland made of nickel plated brass for fixed applications.
The conduit gland can be used in outdoor areas and in mechanical demanding environments.



Material: Brass, nickel plated

Features: High tensile strength
Oil resistant
Corrosion resistant

Temperature range: -50°C up to +300°C

Norm Reference:



Protection class: IP 54

Dimension table:

Part No.	NW	Thread	Inner Diameter mm	Thread length mm	Length mm	SW
5550 1981	10	M12x1,5	5,6	8,0	21,0	13
5550 2001	12	M16x1,5	8,5	10,0	25,5	17
5550 2002	16	M16x1,5	11,5	10,0	26,0	20
5550 2021	16	M20x1,5	11,5	10,0	26,0	22
5550 2022	20	M20x1,5	15,3	10,0	26,3	24
5550 2031	25	M25x1,5	19,1	10,0	32,5	29
5550 2041	32	M32x1,5	26,2	13,0	36,8	36
5550 2051	40	M40x1,5	34,6	14,0	39,0	48
5550 2061	50	M50x1,5	44,7	15,0	42,0	58
5550 2071	63	M63x1,5	54,5	18,0	50,0	70
5550 2073	75	M75x1,5	66,5	20,0	60,0	84

Suitable conduit: SILVYN® LCC-2
SILVYN® LCCH-2

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

AbN
automation

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55501981EN Version: 03	Page 1 of 1
---	---------------------------------------	-------------