

55501982	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® LGS-2-M</b>	

SILVYN® LGS-2-M is a two part conduit gland made of nickel plated brass for swivel applications.

The conduit gland can be used in outdoor areas and in mechanical demanding environments.



**Material:** Brass, nickel plated

**Features:** High tensile strength  
Oil resistant  
Corrosion resistant

**Temperature range:** -50°C up to +300°C

**Norm Reference:**



**Protection class:** IP 54

**Dimension table:**

Part No.	Description	NW	Thread	Inner Ø mm	Thread length mm	Length mm	SW
5550 1982	SILVYN® LGS-2-M 12x1,5	10	M12x1,5	5,6	8,0	30,2	13
5550 2003	SILVYN® LGS-2-M 16x1,5/1	12	M16x1,5	8,5	8,0	32,2	17
5550 2004	SILVYN® LGS-2-M 16x1,5/2	16	M16x1,5	11,5	10,0	34,2	20
5550 2023	SILVYN® LGS-2-M 20x1,5/1	16	M20x1,5	11,5	10,0	34,2	22
5550 2024	SILVYN® LGS-2-M 20x1,5/2	20	M20x1,5	15,3	10,0	35,5	24
5550 2032	SILVYN® LGS-2-M 25x1,5	25	M25x1,5	19,1	12,0	43,7	29
5550 2042	SILVYN® LGS-2-M 32x1,5	32	M32x1,5	26,2	13,0	48,0	38
5550 2052	SILVYN® LGS-2-M 40x1,5	40	M40x1,5	34,2	14,0	51,2	48
5550 2062	SILVYN® LGS-2-M 50x1,5	50	M50x1,5	44,8	15,0	54,2	58
5550 2072	SILVYN® LGS-2-M 63x1,5	63	M63x1,5	54,5	18,0	63,2	70

**Suitable conduit:** SILVYN® LCC-2  
SILVYN® LCCH-2

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

AbN  
automation

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55501982EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------