

55502710	DATA SHEET	
Valid from: 03.07.2018	SILVYN® LGS-2	

SILVYN® LGS-2 is a two part conduit gland made of nickel plated brass for swivel applications.

The conduit gland can be used in outdoor areas and in mechanical demanding environments.



Material: Brass, nickel plated

Features: High tensile strength
Oil resistant
Corrosion resistant

Temperature range: -50°C up to +300°C

Norm Reference:



Protection class: IP 54

Dimension table:

Part No.	Description	NW	Thread	Inner Ø mm	Thread length mm	Length mm	SW
5550 2710	SILVYN® LGS-2 PG 7	10	PG 7	5,6	8,0	30,2	13
5550 2720	SILVYN® LGS-2 PG 9	12	PG 9	8,5	8,0	32,2	17
5550 2730	SILVYN® LGS-2 PG 11	16	PG 11	11,5	10,0	34,2	22
5550 2740	SILVYN® LGS-2 PG 13,5	16	PG 13,5	15,3	10,0	35,5	24
5550 2750	SILVYN® LGS-2 PG 16	20	PG 16	15,3	10,0	35,5	24
5550 2760	SILVYN® LGS-2 PG 21	25	PG 21	19,1	12,0	43,7	29
5550 2770	SILVYN® LGS-2 PG 29	32	PG 29	26,2	13,0	48,0	38
5550 2780	SILVYN® LGS-2 PG 36	40	PG 36	34,2	14,0	51,2	48
5550 2790	SILVYN® LGS-2 PG 48	63	PG 48	54,5	16,0	61,2	70

Suitable conduit: SILVYN® LCC-2
SILVYN® LCCH-2

AbN
automation

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55502710EN Version: 02	Page 1 of 1
---	---------------------------------------	-------------