

| | | |
|---------------------------|---------------------|---|
| 55503179 | DATA SHEET |  |
| Valid from: 03.07.2018 | SILVYN® LGEP | |

SILVYN® LGEP is a two part protection connector for conduits made of nickel plated brass. The connector is suitable for SILVYN® SSUE and can be used in offshore applications and in demanding mechanical environments.



- Material:** Nickel plated brass
- Features:** High mechanical resistant
Oil resistant
Corrosion resistant
Conforms to DIN EN 61386
- Temperature range:** -50 up to +300 °C
- Protection class:** IP 40
- Suitable conduit:** SILVYN® SSUE



Dimension table:

| Part No. | Part name | Nominal size | Length mm | Inner Ø mm | SW |
|-----------|--------------|--------------|-----------|------------|----|
| 5550 3179 | SILVYN® LGEP | 10 | 15 | 5,6 | 13 |
| 5550 3180 | SILVYN® LGEP | 12 | 15,5 | 8,5 | 17 |
| 5550 3181 | SILVYN® LGEP | 16 | 20 | 11,5 | 20 |
| 5550 3182 | SILVYN® LGEP | 20 | 16,5 | 15,3 | 24 |
| 5550 3183 | SILVYN® LGEP | 25 | 20,5 | 19,1 | 29 |
| 5550 3184 | SILVYN® LGEP | 32 | 23,5 | 26,2 | 38 |
| 5550 3185 | SILVYN® LGEP | 40 | 24,8 | 34,2 | 48 |
| 5550 3186 | SILVYN® LGEP | 50 | 30 | 44,8 | 58 |
| 5550 3187 | SILVYN® LGEP | 63 | 33,5 | 54,5 | 70 |
| 5550 3188 | SILVYN® LGEP | 75 | 42 | 66,5 | 84 |

AbN
automation

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

| | | |
|---|---------------------------------------|-------------|
| Creator: M. Wegerer /PDP Released: DAMU1/PDP | Document: DB55503179EN Version: 01 | Page 1 of 1 |
|---|---------------------------------------|-------------|