

55507370	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® FPAX P</b>	

SILVYN® FPAX P is a plug for SILVYN® FPAX T and Y Systems.



- Material:** PA66
- Features:** Fast assembling  
Safety clasp to water and dust
- Temperature range:** -50°C up to +135°C
- Colour:** Black (UV-Resistant)

**Norm Reference:** 

**Note:** Free of halogen, Sulphur and phosphorus

**Protection class:** IP66, IP67 und IP68 (2bar)

**Dimension table:**

Part no.	Part name	Conduit Ø mm	Total height mm	Height of head mm	Head Ø mm
5550 7370	SILVYN® FPAX P	16	25,5	5	27,6
5550 7371	SILVYN® FPAX P	21	27,5	5	33,6
5550 7372	SILVYN® FPAX P	28	33,5	5	42,2
5550 7373	SILVYN® FPAX P	34	34,8	5	48,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

AbN  
automation

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB55507370EN Version: 01	Page 1 of 1
---	---------------------------------------	-------------