

61221035	<b>DATA SHEET</b>	
Valid from: 15.10.2019	<b>SILVYN® TC</b>	

The SILVYN® TC is a protective conduit, which can be applied without screw connection - particularly for thin-walled and thread less housings. SILVYN® TC can be attached with a simple counter nut. Nevertheless we recommend the suitable counter nut our SKINTOP® GMP-GL-M in black.



- Material:** PA6
- Features:** Flexible  
Mechanical protection / Dimension stable  
Quick and easy installation  
Abrasion resistant
- Resistance:** To fuels, mineral oils, lubricants, alkalis and most commercial solvents
- Temperature range:** -40°C up to +120°C (short term to 150°C)
- Colour:** black (UV-Resistant)
- Notes:** Free of halogen  
None declaration-requiring material  
Self-extinguishing HB acc. to UL94
- Protection class:** IP68 (achievable only with an additional flat gasket)

**Dimension table:**

Part no.	Part name	Nominal size	Diameter mm		Thread
			inner	outer	
6440 0823	SILVYN® TC 7,5	7,5	6,6	10,0	M 10x1,0
6440 0824	SILVYN® TC 8,5	8,5	9,8	12,8	M 12x1,5
6440 0825	SILVYN® TC 12	12	12,3	15,7	M 16x1,5
6122 1035	SILVYN® TC 17	17	16,6	21,2	M 20x1,5
6440 0650	SILVYN® TC 22	22	23,1	28,4	M 25x1,5
6440 0651	SILVYN® TC 26	26	28,9	34,5	M 32x1,5
6440 0826	SILVYN® TC 37	37	34	42,2	M 40x1,5
6440 0827	SILVYN® TC 50	50	45,6	53,8	M 50x1,5

- Suitable accessories:** SKINDICHT® JT PTFE (metric)  
SKINTOP® GMP-GL-M  
SILVYN® SPLIT COS  
SILVYN® FLATGASKET  
SILVYN® HOSE CUTTER

For more information see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.



Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB61221035EN Version: 04	Page 1 of 1
---	---------------------------------------	-------------