

6172 1270	<b>DATA SHEET</b>	
Valid from: 08.05.2018	<b>SILVYN® SHRINK BRAID PET</b>	

SILVYN® SHRINK BRAID PET consists of PET protective fibres and has a highly Abrasion-resistant and very good shrink results, also in small radius. The shrinkable braided hose offers protection against dust and liquids, abrasion protection and flexibility. Applicable for easy cable protection, additional insulation, bundling and guiding of cables and wires.



**Material:** PET

**Technical features:**

Profile	Shrinkable woven braid
Nominal size	NW 6 up to NW 70
Temperature range	-40°C up to +150°C
Processing temperature	+180°C up to +220°C
Shrink ratio	2:1

**Additional features:**

Fire classification	HB acc. to UL94
Free of halogen und cadmium	

**Color:** Black



**Approbation:**

**Dimension table:**

Part No.	Nominal width NW	Shrinkable range mm		Wall Thickness mm
		Smallest Diameter	Largest Diameter	
6172 1270	6 - 12	6	12	0,7
6172 1271	12 - 25	12	25	0,7
6172 1272	15 - 30	15	30	0,7
6172 1273	25 - 50	25	50	0,7
6172 1274	35 - 70	35	70	0,7

AbN  
automation

Creator: MAU1/PDP Released: DAMU1/PDP	Document: DB61721270EN Version: 02	Page 1 of 1
--	---------------------------------------	-------------