

68100100	<b>DATA SHEET</b>	
Valid from: 03.07.2018	<b>SILVYN® FLEXILOK 90° M</b>	

SILVYN® FLEXILOK 90° M is a one-part conduit gland with fast fit for a safety assembling. For the demounting we are recommending to use a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions, control cabinet and building wiring.



**Material:** PA66

**Features:** Fast assembling  
Slim design  
Suitable for fine and coarse conduits

**Temperature range:** -40°C up to +120°C

**Colour:** Grey (RAL 7031)  
Black (UV-Resistant)

**Norm reference:**   
UL FILENUMBER E308201

**Note:** Free of halogen, silicon and cadmium

**Protection class:** IP 66

**Dimension table:**

Part no.	Part name	Thread	Conduit Ø mm	Total length mm	Thread length mm	Outer Ø mm	Inner Ø mm
<b>Black</b>							
6810 0100	SILVYN® FLEXILOK 90° M	M 16x1,5	16	44,5	11,5	21	10,5
6810 0105	SILVYN® FLEXILOK 90° M	M 20x1,5/1	16	46	13	21	14
6810 0110	SILVYN® FLEXILOK 90° M	M 20x1,5/2	21	49	13	26	14
6810 0115	SILVYN® FLEXILOK 90° M	M 25x1,5	28	60	15	34	19
6810 0120	SILVYN® FLEXILOK 90° M	M 32x1,5	34	69	16	41	24,5
<b>Grey</b>							
6810 0125	SILVYN® FLEXILOK 90° M	M 16x1,5	16	44,5	11,5	21	10,5
6810 0130	SILVYN® FLEXILOK 90° M	M 20x1,5/1	16	46	13	21	14
6810 0135	SILVYN® FLEXILOK 90° M	M 20x1,5/2	21	49	13	26	14
6810 0140	SILVYN® FLEXILOK 90° M	M 25x1,5	28	60	15	34	19
6810 0145	SILVYN® FLEXILOK 90° M	M 32x1,5	34	69	16	41	24,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

LAPP  
automation

Creator: M. Wegerer /PDP Released: DAMU1/PDP	Document: DB68100100EN Version: 02	Page 1 of 1
---	---------------------------------------	-------------