

68100150	DATA SHEET	
Valid from: 19.01.2026	SILVYN® FLEXILOK 90° PG	

SILVYN® FLEXILOK 90° PG is a one-part conduit gland with fast fit for a safety assembling. For the demounting you are using a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions, control cabinet and building installation.



Material: PA66

Features: Fast assembling
Slim design
Suitable for fine and coarse conduits

Temperature range: -40°C up to +120°C

Colour: Grey (RAL 7031)
Black (UV-Resistant)



Norm reference: UL FILENUMBER E308201

Note: Free of halogen, silicon and cadmium

Protection class: IP 66

Dimension table:

Part no.	Part name	Thread	Conduit Ø mm	Total length mm	Thread length mm	Outer Ø mm	Inner Ø mm
Black							
6810 0150	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0155	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0160	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0170	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0165	SILVYN® FLEXILOK 90° PG	PG 16/1	16	47	11	26	14
6810 0175	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0180	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0185	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5
Grey							
6810 0190	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0195	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0200	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0210	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0205	SILVYN® FLEXILOK 90° PG	PG 16/1	16	47	11	26	14
6810 0215	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0220	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0225	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

ABN
automation

Creator: PDP Released: PDP	Document: DB68100150EN Version: 02	Page 1 of 1
-------------------------------	---------------------------------------	-------------