

## Description

- Inserts for SIGNAL M23 circular connectors
- Universal further processing of the SIGNAL M23 inserts through different packaging units.
- Fully assembled with suitable solder contacts or unpopulated for individual assembly with crimp or solder contacts



## General characteristics

Series	SIGNAL M23
Version	E-part = rotation to the right (clockwise) / P-part = rotation to the left (anticlockwise)
Number of contacts	8+1
Termination method	Crimp termination / Solder termination
Termination cross-section, Crimp termination	0,14 - 1,0 mm <sup>2</sup> (1,0 - 2,5 mm <sup>2</sup> for 2 mm contacts)
Termination cross-section, Solder termination	up to 1,0 mm <sup>2</sup> (up to 2,5 mm <sup>2</sup> for 2 mm contacts)
Temperature range	-25 to +125 °C

## Product variations

Article no.	Version	Contacts included	PU
73002736	P-Part	no	5
73002737	P-Part	no	20
73002738	P-Part	male contacts, solder termination	5
73002739	P-Part	male contacts, solder termination	20
73002740	P-Part	female contacts, solder termination	5
73002741	P-Part	female contacts, solder termination	20
73002742	E-Part	no	5
73002743	E-Part	no	20
73002744	E-Part	male contacts, solder termination	5
73002745	E-Part	male contacts, solder termination	20
73002746	E-Part	female contacts, solder termination	5
73002747	E-Part	female contacts, solder termination	20

## Mechanical characteristics

Cycles of mechanical operation	100
--------------------------------	-----

AbN  
automation

Creator: MANA2/PDP Released: IVSE1/PDP	Document: DB73002736EN Version: 02	Page 1 of 3
---	---------------------------------------	-------------

73002736

**DATA SHEET**Valid from:  
17.09.2018**EPIC® SIGNAL M23 8+1E/P****Electrical characteristics**

Rated voltage	150 V
Rated impulse voltage	2,5 kV
Rated current	20 A (2 mm contacts) 7 A (1 mm contacts)
Contact resistance	< 4 mOhm
Pollution degree	3

**Materials and surfaces**



Insert	PA
Contacts, base material	brass
Contacts, surface	Au

**Approvals**

VDE-Approval, VDE-REG.-Nr.	C24
UL-Approval, E-File-Number	E249137

**Standard**

Safety Standard	IEC 61984
-----------------	-----------

**Drawings**

73002736


# DATA SHEET

Valid from:  
17.09.2018

EPIC® SIGNAL M23 8+1E/P

**LAPP**

Good chemical resistance



Industrial machinery and plant engineering



Mechanical resistance



Assembly time



Robust



Wind Energy



Variety of approval certifications

## Application range

Plant engineering

Measurement and control technology

Apparatus construction

## Remark

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise)

Photographs are not to scale and do not represent detailed images of the respective products.

AbN  
automation