

## Description

- Inserts for SIGNAL M23 circular connectors
- Universal further processing of the SIGNAL M23 inserts through different packaging units.
- Fully assembled with suitable solder contacts or unpopulated for individual assembly with crimp or solder contacts



## General characteristics

Series	SIGNAL M23
Version	E-part = rotation to the right (clockwise) / P-part = rotation to the left (anticlockwise)
Number of contacts	6
Termination method	Crimp termination / Solder termination
Termination cross-section, crimp termination	1,0 - 2,5 mm <sup>2</sup>
Termination cross-section, solder termination	up to 2,5 mm <sup>2</sup>
Temperature range	-25 to +125 °C

## Product variations

Article no.	Version	Contacts included	PU
73002760	P-Part	no	5
73002761	P-Part	no	20
73002762	P-Part	male contacts, solder termination	5
73002763	P-Part	male contacts, solder termination	20
73002764	P-Part	female contacts, solder termination	5
73002765	P-Part	female contacts, solder termination	20
73002766	E-Part	no	5
73002767	E-Part	no	20
73002768	E-Part	male contacts, solder termination	5
73002769	E-Part	male contacts, solder termination	20
73002770	E-Part	female contacts, solder termination	5
73002771	E-Part	female contacts, solder termination	20

## Mechanical characteristics

Cycles of mechanical operation	100
--------------------------------	-----

## Electrical characteristics

Rated voltage	150 V
Rated impulse voltage	4 kV
Rated current	18 A
Contact resistance	< 4 mOhm
Pollution degree	3

AbN  
automation

73002760

# DATA SHEET

Valid from:  
17.09.2018

EPIC® SIGNAL M23 6 E/P



## Materials and surfaces

Insert	PA
Contacts, base material	brass
Contacts, surface	Au



## Approvals

VDE-Approval, VDE-REG.-Nr.	C24
UL-Approval, E-File-Number	E249137

## Standard

Safety Standard	IEC 61984
-----------------	-----------

## Drawings





Good chemical resistance



Industrial machinery and plant engineering



Mechanical resistance



Assembly time



Robust



Wind Energy



Variety of approval certifications

## Application range

Plant engineering

Measurement and control technology

Apparatus construction

## Remark

The inserts are suitable for both male and female contacts. For a complete connection, you will need one P-component and one E-component. P-component = left turning (anticlockwise), E-component = right turning (clockwise)

Photographs are not to scale and do not represent detailed images of the respective products.

AbN  
automation