

| | | |
|---------------------------|---|---|
| CE6326 | DATA SHEET |  |
| Valid from: 14.11.2018 | EPIC® CE6326 RJ45 Connector for MCS 8 RJ45 | |

Description

- The mixed assembly guarantees high flexibility. For applications in mechanical and plant engineering, for printing machines and slide-in technology.
- RJ45 connector for use in the module MCS 8 RJ45



General Characteristics

| | |
|---------------------|--|
| Series | MC Module |
| Version | Male |
| Number of Contacts | 8 |
| Termination Methods | IDC/piercing termination: Cat 5, AWG 24-26 |
| Temperature Range | -20°C to +85°C |

Mechanical Characteristics

| | |
|-------------------------------|-----|
| Cycle of mechanical operation | 100 |
|-------------------------------|-----|

Electrical Characteristics

| | |
|-------------------|------------|
| Rated Voltage | max. 125V |
| Rated Current | max. 1.5 A |
| Degree of Soiling | 3 |

Materials and Surfaces

| | |
|---------|---------------------------|
| Contact | Copper alloy, gold-plated |
|---------|---------------------------|



Automation



Industrial machinery and plant engineering



Wind Energy

Application range

Plant engineering
Control engineering

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

AbN
automation

| | | |
|---|-------------------------------------|-------------|
| Creator: MANA2/PDP Released: IVSE1/PDP | Document: DBCE6326EN Version: 01 | Page 1 of 1 |
|---|-------------------------------------|-------------|