

VISION VXL 454

Order Code: 1344712

Hand Detection Safety Light Curtain with Automatic/Manual Restart and EDM



Safety level

Type 2 - PL c

Protected height (mm)

460

Resolution (mm)

40

Max. range (m)

8

Restart

Built-in - User selectable
automatic or manual

Functioning system

Emitter / Receiver

Technical Description

Safety Light Curtain: Type 2, SILCL 1, PL c, Cat. 2

Cross Section: 35 x 45 mm

Hardware configuration: no programming necessary, easy to install and replace

Connection and configuration through M12 connectors

Unshielded cables up to 100 m can be used to connect the Safety Light Curtain

What's in the Box: Emitter, Receiver and Standard Fastening Brackets

Features

Safety level	Type 2 - PL c
Protected height (mm)	460
Resolution (mm)	40
Max. range (m)	8
Restart	Built-in - User selectable automatic or manual
Functioning system	Emitter / Receiver
Safety level (SIL / PL)	Type 2 - SILCL 1 - PL c - Cat. 2
Operating temperature (°C)	0 ... 55
Response time (ms)	11
Number of beams	15
Max. length of the connection cables (m)	100
Signalling	LEDs for light curtain's status and diagnostics
Safety output type	2 fail-safe PNP (500 mA at 24 VDC) with protection against short circuit, overload and reverse polarity
Connections	M12 5-pole connector (emitter), M12 8-pole connector (receiver)
MTTFD (ISO13849) years	100
PFHD (IEC 61508)	3,79E-08
Safety outputs	2 OSSD PNP (500 mA at 24 VDC)
Safety functions	Integrated
Detection	Hand
Operating Range (m)	Selectable: 0 ... 6 m - low range / 1 ... 18 m - high range

VISION VXL 454

Protective enclosures	None
Packaging dimensions HxLxW (mm)	145 x 600 x 200
Product class	B
Custom tariff	85365019

Electrical data


Power supply (VDC)	24 $\pm$ 20%
--------------------	--------------

Mechanical data

Overall height (mm)	561
Cross section dimensions (mm)	35 x 45
Degree of protection	IP65
Fastening	Back slot, side slot with set of LS type brackets (included) or to the top and lower end with SFB swivel brackets (optional)

Technical drawings

A (Overall height) = 561 mm



Certificates

